





SABLE

SAND FFFECT • TRADITIONIAL FFFECTS FOR A MODERN INTERIOR

APPLICATION INSTRUCTIONS PRIMER - BASE - FINISH





SABLE PRIMER

The colour of the cachemire SABLE Primer is white; it strengthens the surface and reduces the suction for an even end-result.

Coverage: 8m²/L

Drying time: 1.5 hours at 20°C/60°r.h.





TAPING UP BEFORE APPLYING
THE SABLE PRIMER



APPLY SABLE PRIMER WITH ROLLER



SABLE BASE

Cloud effect

A new velvet matt interior wall paint with a fine sand structure.

Prolonged open time (2-3 hours) - no tendency to show overlaps - good covering power - odour-less - closed paint film - homogenous repartition of the sand in the paint without tendency to settle in the can.

Coverage: 8m²/kg

Drying time: 4 hours at 20°C/60°r.h.









APPLY PAINT WITH A SPATULA
WHEREAFTER YOU CAN PARTITION
THE PAINT WITH A SPAITER

APPLY THE PAINT CROSSVVISE



SABLE BASE Cloud effect





INNER LEFT CORNER







SABLE BASE Vertical technique









SABLE FINISH

Cachemire SABLE Finish is a transparent varnish that gives extra protection to the decorative sand structure. It will become washable, scratch-proof and hard-wearing.

Coverage: 12-14m²/L

Drying time: 30 min. at 20°C/60°r.h.

Apply with a spalter or roller.











Be inspired by cachemire SABLE, a new velvet matt interior wall paint with fine sand structure, suitable for all spaces in any living style. With cachemire SABLE you create a decorative sand effect that gives all your walls a warm, traditional yet contemporary feel.

Cachemire SABLE creates soft gradations in colour and the relief of nature. Cachemire SABLE masks slight unevennesses by covering with a finely textured layer with depth and a tactile aspect. The natural, earthy look also evokes the organic tints of stone and sand.