

Quality Paints since 1845
MATHYS[®]



AMW FUNGICIDAL WASH

Effective algae, fungi and dirt remover

- Removes and prevents growth from fungi and algae
- HSE approved biocide
- Ready-mix product
- Does not harm glass or PVC
- For bituminous substrates, concrete, masonry, plaster and woodwork

AMW FUNGICIDAL WASH

BESKRIVELSE

Ready-mix fungi and algae remover for walls and roofs.

ANBEFALET BRUG

As a masonry surface fungicidal wash for professional use against mould, fungi, moss, etc. Also suitable for treatment of similarly affected roof surfaces.

TEORETISK FORBRUG

5 m²/l

PRAKTISK FORBRUG

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

FORBEHANDLING AF OVERFLADEN

All mould, fungi, lichens etc. should be given a saturated coat of AMW before their complete removal (to kill spores). Remove debris by power washing or use of a stiff brush. The whole area should then be given a second coat of AMW and allowed to dry (to render the substrate sterile).

BRUGSANVISNING

Apply AMW abundantly, preferably by brush, and wait 12 hours. Dry-brush and remove dust prior to painting, or clean with high-pressure water and let the surface dry. Affected by heavy rainfall for at least 4 hours after application. If doubtful re-apply. Ensure residues are substantially diluted with water before entering drains etc.

ANVENDELSBETINGELSER

Minimum 8°C and maximum 80% R.H.

PÅFØRING OG FORTYNDING: PENSEL

Do not dilute.

PÅFØRING OG FORTYNDING: LUFTATOMISERET SPRØJTE

"Coarse" spray such as a pneumatic garden spray. Do not dilute.

RENGØRING AF Udstyr/SPILD

Water.

BEMÆRKNINGER

This fungicidal product is only available in the UK, so not available for Export. HSE-approval no. 9225

SIKKERHEDSDATA

VOC-niveau:

0 g/l

Bemærkninger om sikkerhed:

Consult Safety Data Sheet and Safety Information printed on the can.

Use biocides safely. Always read the label and product information before use.

PH

4,50

HOLDBARHED

Minimum of 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C. **Protect material from frost.**

Udstedelsesdato: 16/04/2024

Tilgængelige farver og pakningsstørrelser: Der henvises til den respektive produktside på www.rust-oleum.eu for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

Ansvarsfraskrivelse: Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europes anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra www.rust-oleum.eu eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu