

Quality Paints since 1845
MATHYS[®]



AMW FUNGICIDAL WASH

Effective algae, fungi and dirt remover

- Removes and prevents growth from fungi and algae
- HSE approved biocide
- Ready-mix product
- Does not harm glass or PVC
- For bituminous substrates, concrete, masonry, plaster and woodwork

AMW FUNGICIDAL WASH

DESCRIPTION

Ready-mix fungi and algae remover for walls and roofs.

RECOMMENDED USE

As a masonry surface fungicidal wash for professional use against mould, fungi, moss, etc. Also suitable for treatment of similarly affected roof surfaces.

THEORETICAL CONSUMPTION

5 m²/l

PRACTICAL CONSUMPTION

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

SURFACE PREPARATION

All mould, fungi, lichens etc. should be given a saturated coat of AMW before their complete removal (to kill spores). Remove debris by power washing or use of a stiff brush. The whole area should then be given a second coat of AMW and allowed to dry (to render the substrate sterile).

DIRECTIONS FOR USE

Apply AMW abundantly, preferably by brush, and wait 12 hours. Dry-brush and remove dust prior to painting, or clean with high-pressure water and let the surface dry. Affected by heavy rainfall for at least 4 hours after application. If doubtful re-apply. Ensure residues are substantially diluted with water before entering drains etc.

APPLICATION CONDITIONS

Minimum 8°C and maximum 80% R.H.

APPLICATION & THINNING: BRUSH

Do not dilute.

APPLICATION & THINNING: AIR-ATOMISED SPRAY

"Coarse" spray such as a pneumatic garden spray. Do not dilute.

CLEANING OF EQUIPMENT / SPILLS

Water.

REMARKS

This fungicidal product is only available in the UK, so not available for Export. HSE-approval no. 9225

SAFETY DATA

VOC level: 0 g/l
Remarks regarding safety: Consult Safety Data Sheet and Safety Information printed on the can.
Use biocides safely. Always read the label and product information before use.

PH

4,50

SHELF LIFE

Minimum of 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C. **Protect material from frost.**

Date issued: 07/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu