



BRUSH CLEANER

Renews & restores used and hardened brushes

- Fast Acting
- Contains Powerful Detergents
- Effective on : Shellac, Water & Solvent Based Varnishes and Lacquers, Enamel (Alkyd) Gloss Paints, Water Based Acrylic and Vinyl Paints. (not suited for the cleaning of 2 pack paints)

BRUSH CLEANER

DESCRIPTION

This professional formula dissolves all kind of paints and varnishes and restores brushes without any effort to a nearly new condition.

RECOMMENDED USE

- Place the brush into a clean empty container then add Brush Cleaner to cover the bristles(and metal ferrule if required).
- 2. Soak for up to 4 hours, periodically agitating to loosen up the dried on paint.
- 3. Remove excess paint residues when possible and re-immerse into Brush Cleaner ifnecessary.
- 4. When the paint is removed rinse the brush thoroughly several times under warm (not hot)running water.
- 5. Finally shake off excess water and hang the brush to dry before use.

DIRECTIONS FOR USE

Shake Brush Cleaner thoroughly before use.

Not suitable for the cleaning of two pack paints. Do not soak brushes in Brush Cleaner for more than 4 hours. Brush Cleaner may remove the dye or colouring from coloured brushes and dark natural bristle.

CLEANING OF EQUIPMENT / SPILLS

Remove as much product from application equipment as possible before washing with warm water. Do not empty into drains or watercourses. Some local authorities have special facilities for the disposal of waste coatings.

REMARKS

Appearance: Slightly cloudy liquid, may separate slightly hence must be shaken thoroughly before use.

Brush cleaner is suitable for Zinsser BIN (based on Shellac).

SHELF LIFE

Minimum of 3 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5 and 30° C.

Date issued: 07/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.

Zilverenberg 16 5234 GM 's-Hertogenbosch The Netherlands T: +31 (0) 165 593 636 F: +31 (0) 165 593 600 into@pust_oleum Tor Coatings Ltd (Rust-Oleum Industria Shadon Way, Portobello Ind. Estate Birtley, Chester-le-Street DH3 2RE United Kingdom T: +44 (0)1914 113 146 F: +44 (0)1914 113 147 Rust-Oleum France S.A.S. 38, av. du Gros Chêne 95322 Herblay France T: +33(0) 130 40 00 44 F: +33(0) 130 40 99 80 info@rust-oleum.eu N.V. Martin Mathys S.A. Kolenbergstraat 23 3545 Zelem Belgium T: +32 (0) 13 460 200 F: +32 (0) 13 460 201 info@rust-oleum.eu