

Quality Paints since 1845
MATHYS[®]



CACHEMIRE SABLE BASE

Traditional effects for a modern interior

- Long open time (1 - 2 hours)
- No tendency to overlap
- Splash free
- Good covering power
- Odourless



CACHEMIRE SABLE BASE

DESCRIPTION

Cachemire Sable Base is a new velvety matt interior wall paint with fine sand structure, suitable for all spaces in any living style. With Cachemire Sable Base you create a decorative sand effect that gives all your walls a warm, traditional yet contemporary feel.

TECHNICAL DATA

Density (g/cm ³):	1,3 - 1,4
Solids Content in weight:	± 48%
Solids content in volume:	± 30%

DRY TIMES BY 20° C/RH 50%

Touch dry:	4 h
Dry to recoat:	24 h
Fully cured:	± 1 day

APPLICATION CONDITIONS

> 10°C, < 80% R.H.

SAFETY DATA

VOC level:	179 g/l
VOC ready mix:	179 g/l
VOC category:	A/i
VOC limit:	200 g/l

SHELF LIFE

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 23/01/2023

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu