



## CACHEMIRE SABLE BASE

### Traditionel effects for a modern interior

- Long open time (1 - 2 hours)
- No tendency to overlap
- Splash free
- Good covering power
- Odourless

# CACHEMIRE SABLE BASE

## DESCRIPTION

Cachemire Sable Base is a new velvety matt interior wall paint with fine sand structure, suitable for all spaces in any living style. With Cachemire Sable Base you create a decorative sand effect that gives all your walls a warm, traditional yet contemporary feel.

## TECHNICAL DATA

Density (g/cm³):	1,3 - 1,4
Solids Content in weight:	± 48%
Solids content in volume:	± 30%

## DRY TIMES BY 20° C/RH 50%

Touch dry:	4 h
Dry to recoat:	24 h
Fully cured:	± 1 day

## APPLICATION CONDITIONS

> 10°C, < 80% R.H.

## SAFETY DATA

VOC level:	179 g/l
VOC readymix:	179 g/l
VOC category:	A/i
VOC limit:	200 g/l

## SHELF LIFE

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 07/02/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)