



DIVALO

Varnish for the finishing touch of interior wall paints.

- Not yellowing
- Smooth satin views
- Washable

DIVALO

DESCRIPTION

Water based acrylic varnish. For the finishing touch of interior wall paints when a high mechanical resistance is required.

RECOMMENDED USE

Finish on indoor paints and decorative paint systems when a high mechanical resistance is required. Recommended as a topcoat on decorative paint systems (Fair-Dekor).

TECHNICAL DATA

Density (g/cm³):	1,02 - 1,06
Gloss Level:	Satin
Gloss level at 60°:	Satin Gloss: ± 20%
Solids Content in weight:	30 - 33 %
Solids content in volume:	27,5 - 30,5 %

DRY TIMES BY 20° C/RH 50%

Touch dry:	30 minutes
Dry to recoat:	4 hours
Fully cured:	± 1 week

RECOMMENDED WET FILM THICKNESS

± 70 µm

RECOMMENDED DRY FILM THICKNESS

± 20 µm

THEORETICAL CONSUMPTION

12 - 14 m²/l

PRACTICAL CONSUMPTION

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

SURFACE PREPARATION

Clean and degrease substrate. The paint coats or systems that have to be protected have to be dry and/or fully cured.

DIRECTIONS FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

APPLICATION CONDITIONS

> 5°C, max. 80% R.H.

APPLICATION & THINNING: BRUSH

Apply in 1 or 2 coats with flat brush. If necessary dilute with water.

APPLICATION & THINNING: ROLLER

Apply in 1 or 2 coats with lacquer. If necessary dilute with water.

APPLICATION & THINNING: AIRLESS SPRAY

Nozzle: 09 - 013 / Pressure: 180 bars.

APPLICATION & THINNING: AIR-ATOMISED SPRAY

If necessary dilute with water.

CLEANING OF EQUIPMENT / SPILLS

Water.

SAFETY DATA

VOC level:	90 g/l
VOC readymix:	90 g/l
VOC category:	A/e
VOC limit:	130 g/l
Grenelle:	A+
Remarks regarding safety:	Consult Safety Data Sheet and Safety Information printed on the can.

SHELF LIFE

Minimum of 2 years from date of production in unopened cans. If stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 12/06/2023

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu