Quality Paints since 1845
MATHYS®

## FASSICRYL SATIN SPRAY

# Sprayable water-based silky gloss lacquer

- Sprayable (airless and airmix)
- Skin grease-resistant
- Scratch-resistance and easy to clean
- Excellent flow viscosity
- Good colour and gloss retention

# FASSICRYL SATIN SPRAY

## DESCRIPTION
Fassicryl Satin Spray is a top-quality sprayable water-based silky gloss indoor lacquer based on PU acrylate with excellent coverage. Suitable as a top layer to cover wood as well as any pre-treated surface such as plastic or metal. Fassicryl Satin Spray is scratch-resistant and skin grease-resistant. The paint is slightly thixotropic, has excellent flow viscosity and good colour and gloss retention. Can be applied with a brush.

## ODPORÚČANÉ POUŽITIE
This sprayable water-based scratch-free silky gloss lacquer is suitable as a top layer to cover wood as well as any properly pre-treated surface such as plastic or metal.

## ODPORÚČANÝ SYSTÉM
Priming with Fassicryl Primer. Use Fassicryl Sealing Primer on bleeding wood types. Finish with a Fassicryl lacquer.

## TECHNICAL_DATA

| | |
|---|---|
| Hustota (g/cm³): | 1,20 (white - wit - blanc - weiß) |
| Úroveň lesku: | Satin |
| Úroveň lesku pri 60º: | 45-50% (white - wit - blanc - weiß) |
| Obsah pevných látok v objeme: | 35% (white - wit - blanc - weiß) |

## DRY TIMES BY 20º C/RH 50%

| | |
|---|---|
| Na dotyk suché: | 1 hour |
| Suchý na opätovné natieranie: | 6 hours |

## ODPORÚČANÁ HRÚBKA MOKRÉHO FILMU
150-250 µm

## TEORETICKÁ SPOTREBA
4-6 m²/l/coat

## PRAKTICKÁ VÝDATNOSŤ
Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

## PRÍPRAVA POVRCHU
The surface must be dry and free of dust and grease. Round off sharp edges so that you can apply a good coating.
New work: priming with Fassicryl Primer. Use Fassicryl Sealing Primer on bleeding wood types.
Existing work: lightly sand old and properly adhesive coats. Remove loose, cracked or flaky coats. Treat exposed locations as new wood.

## NÁVOD NA POUŽITIE
To ensure homogeneity, thoroughly stir prior to use.

## PODMIENKY APLIKÁCIE
> 8°C, < 80% R.H.

## APLIKÁCIA A RIEDENIE: ŠTETEC
This sprayable paint can also be applied with a brush. Apply undiluted with brush with synthetic bristles.

## APLIKÁCIA A RIEDENIE: BEZVZDUCHOVÉ STRIEKANIE
Nozzle: 0.009 - 0.012 / Pressure: Ca. 70 bars
The product is ready for use; do not dilute.

## APLIKÁCIA A RIEDENIE: VZDUCHOVO ATOMIZOVANÝ SPREJ
Air-assist - Nozzle: 0.009 - 0.012 / Pressure: Ca. 60 bars / Air pressure: Ca.2 bars
The product is ready for use; do not dilute.

## ČISTENIE ZARIADENIA / POSTRIEKANIE
Clean the material with water and dispose of the residue appropriately.

## POZNÁMKY
Do not apply paint at temperatures below 8°C. The surface temperature must be at least 3°C above the dew point.
Scratch-resistance is achieved after 15-30 days depending on the colour.

## SAFETY DATA

| | |
|---|---|
| Úroveň VOC: | 30g/l |
| VOC readymix: | 30g/l |
| Kategória VOC: | IIA/d |
| Limit VOC: | 130g/l |
| Poznámky k bezpečnosti: | Consult Safety Data Sheet and Safety Information printed on the can. |

## SKLADOVATEĽNOSŤ
Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5 and 35°C.

**last_updated:** 22/06/2026

**footer_data_colors_pack_sizes:** footer_data_colors_pack_sizes.value

**footer_data_disclaimer:** footer_data_disclaimer.value


**Rust-Oleum Netherlands B.V.**
Europalaan 9
5232 BC 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu