



MATHY+ MAT

High quality matt paint

- High opacifying and filling power
- Fine grain, beautiful and regular appearance
- No recovery, long open time
- Easy to clean
- Wet friction resistance: Class 2 (DIN EN 13300)

MATHY+ MAT

DESCRIPTION

Filling matt paint in high quality water dispersion for interior walls. Applicable on most mineral substrates.

RECOMMENDED USE

Peinture décorative pour murs intérieurs, pour bâtiments privés ou publics.

RECOMMENDED SYSTEM

The surface must be clean, dry and consistent. Substrates that are porous must first be impregnated with MATHY+ Primer. Moisture or nicotine stains must first be insulated with Pegaprim Isofix or Pegamat RL. Highly porous substrates and smooth plasters must first be impregnated with a layer of the 1/1 mixture of Pegafix and MATHY+ Matt.

TECHNICAL DATA

Density (g/cm ³):	1.47 g/cm ³
Gloss Level:	Matt
Gloss level at 85°:	<5%
Solids content in volume:	36%
Wet Scrub Resistance (EN 13300):	Class 2 (≥ 5 µm and <20 µm at 200 strokes)

DRY TIMES BY 20° C/RH 50%

Touch dry:	2 hours
Dry to recoat:	6 hours

RECOMMENDED WET FILM THICKNESS

111 µm

RECOMMENDED DRY FILM THICKNESS

38 µm

THEORETICAL CONSUMPTION

8-10 m²/l

PRACTICAL CONSUMPTION

The consumption depends on many factors such as the roughness or porosity of the substrate and product losses during application.

DIRECTIONS FOR USE

To obtain good homogeneity, mix the product well before use.

APPLICATION CONDITIONS

> 8°C, < 80% R.H.

APPLICATION & THINNING: BRUSH

Apply undiluted.

APPLICATION & THINNING: ROLLER

Apply undiluted. High density 12mm polyester microfiber roller or any other suitable roller.

APPLICATION & THINNING: AIRLESS SPRAY

Apply undiluted. Nozzle: 017 - 019 / Pressure: 170 - 200 bar

CLEANING OF EQUIPMENT / SPILLS

Water

REMARKS

The product is ready to use, diluting is not necessary. AFNOR classification (NF T 36-005): Family I Class 7a2.

SAFETY DATA

VOC level:	1 g/l
VOC category:	IIA/a
VOC limit:	30 g/l
Remarks regarding safety:	Consult the Safety Data Sheet and the safety information printed on the can.

SHELF LIFE

Minimum of 1 year from date of production in unopened cans, if stored in dry, well ventilated areas, not indirect sunlight at temperatures between 5 and 35°C.

Date issued: 07/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu