



MATHY+ PRIMER

Highly covering absorption regulator primer

- Strengthens support and reduces absorption
- Quick drying
- Neutralizes differences in porosity of the substrate
- Avoids smears (matt and shiny shades) in the top coat
- Very good covering power

MATHY+ PRIMER

DESCRIPTION

Aqueous dispersion primer based on acrylic resins for interior walls and ceilings. A covering primer that neutralizes differences in the absorption of the substrate. Applicable on most substrates, before painting them with water-thinnable paints. Quick drying, avoids smears (matt and glossy stains) in the top coat, improves the adhesion of the top coat.

RECOMMENDED USE

Inside, on various unpainted porous surfaces (e. g. bricks, plaster, concrete) before painting them with water-thinnable paints.

RECOMMENDED SYSTEM

The substrates must be clean and dry. Porous substrates and smooth plasters must first be impregnated with a coat of Pegafix. Water or nicotine stains must be masked with Pegamat RL or Pegaprim Isofix.

TECHNICAL DATA

Density (g/cm ³):	1.35 g/cm ³ (blanc)
Gloss level at 60°:	5%
Solids Content in weight:	58% (blanc)
Solids content in volume:	45% (blanc)

DRY TIMES BY 20° C/RH 50%

Touch dry:	1.5 hours
Dry to recoat:	2 - 3 hours
Fully cured:	1 week

RECOMMENDED WET FILM THICKNESS

100 µm

RECOMMENDED DRY FILM THICKNESS

45 µm

THEORETICAL CONSUMPTION

8 - 10 m²/l

PRACTICAL CONSUMPTION

The consumption depends on many factors such as the roughness or porosity of the substrate and product losses during application.

DIRECTIONS FOR USE

To obtain good homogeneity, mix the product well before use.

APPLICATION CONDITIONS

Application at a temperature of min. 5°C and a R.H. of max. 80%.

APPLICATION & THINNING: BRUSH

Apply undiluted.

APPLICATION & THINNING: ROLLER

Apply undiluted. Textured polyamide roller 12-14mm or any other suitable roller.

APPLICATION & THINNING: AIRLESS SPRAY

Apply undiluted. Nozzle: 011 - 015 / Pressure: 180 - 200 bar.

APPLICATION & THINNING: AIR-ATOMISED SPRAY

Apply undiluted.

CLEANING OF EQUIPMENT / SPILLS

Water

REMARKS

The product is ready to use, diluting is not necessary. AFNOR classification (NF T 36-005): Family I Class 7b2.

SAFETY DATA

VOC level:	30 g/l max.
VOC ready mix:	30 g/l max.
VOC category:	A/g
VOC limit:	30 g/l
Remarks regarding safety:	Consult the Safety Data Sheet and the safety information printed on the can.

SHELF LIFE

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not indirect sunlight at temperatures between 5 and 35°C.

Date issued: 07/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu