

Quality Paints since 1845
MATHYS[®]



MATHY+ SATIN

High quality acrylic paint

- Fast drying
- Applicable on most substrates including glass fabric
- Slightly dappled appearance
- Opaque
- Lessivable: Class 1 (DIN EN 13300)

MATHY+ SATIN

DESCRIPTION

Acrylic paint in aqueous dispersion for ceilings and interior walls. Applicable on most substrates, also on the glass fabric. Very filling. Gives a satin aspect slightly poached, washable, good hiding power.

RECOMMENDED USE

Decorative painting for interior walls and ceilings, for private or public buildings.

RECOMMENDED SYSTEM

The surface must be clean, dry and consistent. Substrates that are porous must first be impregnated with Mathy+ Primer. Moisture or nicotine stains must first be insulated with Pegaprim Isofix or Pegamat RL. Highly porous substrates and smooth plasters must first be impregnated with a layer of the 1/1 mixture of Pegafix and MATHY+ Satin.

TECHNICAL DATA

Density (g/cm ³):	1,32 g/ml
Gloss level at 60°:	30%
Solids Content in weight:	57 % (blanc)
Solids content in volume:	44 % (blanc)
Wet Scrub Resistance (EN 13300):	Class 1 (<5 µm abrasion at 200 strokes)

DRY TIMES BY 20° C/RH 50%

Touch dry:	1 hour
Dry to recoat:	3 hours
Fully cured:	± 2 days

RECOMMENDED WET FILM THICKNESS

125 µm

RECOMMENDED DRY FILM THICKNESS

55 µm

THEORETICAL CONSUMPTION

7-12 m²/liter

PRACTICAL CONSUMPTION

The consumption depends on many factors such as roughness, porosity and application conditions.

SURFACE PREPARATION

Cracks, holes: fill and seal with ElastoPro.

DIRECTIONS FOR USE

To ensure good homogeneity, mix the product well before use.

APPLICATION CONDITIONS

The work will be carried out in accordance with DTU 59-1. Minimum temperature 5°C, maximum relative humidity 80%.

APPLICATION & THINNING: BRUSH

Synthetic brush

APPLICATION & THINNING: ROLLER

High density 12mm polyester microfiber roller or 14mm textured polyamide roller or any other suitable roller.

CLEANING OF EQUIPMENT / SPILLS

Water

REMARKS

For best results, use a 12mm high density polyester microfiber roller. The product is ready to use, diluting is not necessary. AFNOR classification (NF T 36-005): Family I Class 7b2.

SAFETY DATA

VOC level:	29 g/l max.
VOC readymix:	50 g/l max.
VOC category:	A/b
VOC limit:	100 g/l
Remarks regarding safety:	Consult the information on the label, and the safety data sheet available on our website.

SHELF LIFE

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not indirect sunlight at temperatures between 5 and 35°C.

Date issued: 07/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu