MURFILL® WP INTER

Elastic intermediate layer for façade renovation

- Waterproofing system
- Acrylate system, very smooth
- Very durable, guarantee
- Very smooth paint film, crack bridging
- Permanently elastic

MURFILL® WP INTER

DESCRIPTION
Filling interlayer for waterproofing system with Murfill® WP Plus NF.

RECOMMENDED SYSTEM
Very smooth interlayer for waterproofing systems in combination with Murfill WP Plus NF.
Crack bridging from 0.2 mm to 2 mm

TECHNICAL DATA

Density (g/cm³):	1,2 (± afhankelijk van kleur)
Solids Content in weight:	Gewicht: 66 % (± afhankelijk van kleur)

THEORETICAL CONSUMPTION
250 to 500 g/m² depending on the system.

PRACTICAL CONSUMPTION
Consumption is theoretical and depends on many factors such as roughness and porosity of the substrate and application conditions.

DIRECTIONS FOR USE
Before use, the coatings must be intensively stirred to a good homogeneity

APPLICATION CONDITIONS
Minimum temperature 5 ° C, maximum temperature 35 ° C and maximum relative humidity 80%. No condensation during the drying time. A low temperature and/or a high relative humidity prolong the drying time.

APPLICATION & THINNING: BRUSH
- Synthetic brushes for water-based paints.
- 15% water when used as a primer

APPLICATION & THINNING: ROLLER
- Textured polyamide rolls 20 mm or long-haired brushes according to the roughness of the surface.
- 15% water when used as a primer

SAFETY DATA

VOC level:	139 g/l max.
VOC category:	A/i
VOC limit:	140 g/l (2010)
Remarks regarding safety:	Consult the relevant product safety sheet and the information on the packaging.

SHELF LIFE
Minimum of 2 years from the date of production in unopened, original packaging, if stored in dry, well-ventilated areas, not in direct sunlight, at temperatures between 5 ° and 35 ° C.

Date issued: 14/09/2022

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu