

Quality Paints since 1845  
**MATHYS**<sup>®</sup>



## MURFILL<sup>®</sup> WP PLUS NF

# Elastic waterproofing system

- UV-crosslinking system, acrylic
- Very durable system, guarantee
- Very flexible paint film, crack-bridging
- Permanently elastic
- Waterproof



# MURFILL® WP PLUS NF

## DESCRIPTION

Smooth, semi-thick elastic cladding for facades. Based on acrylic resins with UV-cross-linking system, for waterproofing facades. Water based.

## RECOMMENDED USE

Waterproofing of facades, crack bridging from 0.2 mm to 2 mm

## TECHNICAL DATA

Density (g/cm <sup>3</sup> ):	1,5 (± afhankelijk van kleur)
Gloss Level:	Matt
Gloss level at 85°:	2%
Solids Content in weight:	74 % (± afhankelijk van kleur)
Solids content in volume:	62 % (± afhankelijk van kleur)

## THEORETICAL CONSUMPTION

500 g/m<sup>2</sup>/coat

## PRACTICAL CONSUMPTION

The consumption is theoretical and depends on many factors such as roughness and porosity of the substrate and the application conditions.

## SURFACE PREPARATION

The surface must be completely clean, dry and healthy. In the event of contamination by microorganisms, pre-clean with an anti-moss solution.

## DIRECTIONS FOR USE

Before use, the coatings must be stirred intensively to a good homogeneity

## APPLICATION CONDITIONS

Minimum temperature 5 °C, maximum temperature 35 °C and maximum relative humidity 80%. No condensation during the drying time. A low temperature and/or a high relative humidity extend the drying time.

## APPLICATION & THINNING: BRUSH

- Synthetic brushes for water-based paints.
- 15% water when used as a primer

## APPLICATION & THINNING: ROLLER

- 20 mm textured polyamide rolls or long-haired brushes according to the roughness of the surface
- 15% water when used as a primer

## CLEANING OF EQUIPMENT / SPILLS

water

## SAFETY DATA

VOC level:	139 g/l max.
VOC category:	A/i
VOC limit:	140 g/l (2010)
Remarks regarding safety:	Consult the relevant product safety sheet and the information on the packaging.

## SHELF LIFE

Minimum of 2 years from production date in unopened, original packaging, if stored in dry, well-ventilated areas, not in full sun, at temperatures between 5 ° and 35 ° C.

Date issued: 14/09/2022

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
[info@rust-oleum.eu](mailto:info@rust-oleum.eu)