MATHYS®
Quality Paints since 1845

PARACEM® DECO PLAFOND

One-coat ceiling paint

- Exceptional high covering power (covers mostly in 1 layer)
- Uniform matt finish without laps
- Delayed drying (enables to paint large surfaces)
- Odourless
- Extra matt

PARACEM® DECO PLAFOND

BESKRIVNING
Paracem Deco Plafond is a super covering and extra matt acrylic paint for ceilings and inner walls. Applicable on most mineral substrates.

REKOMMENDERAD ANVÄNDNING
For indoor walls and ceilings: on plaster, plasterboard, rendering, bricks, concrete, etc. as well as on old paints, wallpaper, ingrain wallpaper, etc.

TEKNISK DATA

Densitet:	1,41 - 1,45
Glansnivå:	Matt
Glansnivå vid 60°:	Matt: 2%
Torrsubstansvikt:	52 - 54%
Torrsubstansvolym:	32 - 34%

TORKTIDER VID 20°C/RELATIV LUFTFUKTIGHET 50%

Beröringstorr:	2 hours
Torktid:	4 hours
Fullt härdad:	1 day

REKOMMENDERAD VÅTFILMSTJOCKLEK
140 µm

REKOMMENDERAD TORRFILMSTJOCKLEK
45 µm

ÅTGÅNG
6 - 8 m²/l per coat

ÅTGÅNG INFORMATION
Practical coverage depends on many factors such as porosity, roughness of the substrate and material losses during application.

FÖRBEREDELSER
The surface must be dry and free of dust and grease.
You can paint Paracem® Deco Soft Plafond directly over clean, old layers of paint that are still in good condition and onto surfaces that are not too porous. You must treat porous surfaces with Paracem® Deco Primer first.
Highly porous surfaces, smooth plaster, and water-resistant plasterboard must be impregnated with Pegafix first.
Nicotine and water stains stains must be isolated first with Pegamat® RL orZinsser primers Bulls Eye 123 or 123 Plus.
Unpainted woodwork must be treated appropriately first and a priming coat must be applied (e.g. Fassiprim Aqua or Zinsser primers Bulls Eye 123 or 123 Plus).
Metal objects without rust spots are to be pre-treated with Pegalink®, orZinsser primers Bulls Eye 123.

APPLICERING
To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

APPLICERINGSFÖRHÅLLANDEN
Minimum 5°C / Maximum 80% R.H.

REDSKAP
Apply undiluted.

APPLICERING OCH SPÄDNING: ROLLER
Apply undiluted.

APPLICERING OCH SPÄDNING: AIRLESSPRUTA
If necessary, dilute with some water.
Nozzle: 011 - 013 / Pressure: 200 bars, dilute with maximum 3% volume water.

APPLICERING OCH SPÄDNING: TRYCKLUFTSSPRUTA
Not recommended.

RENGÖRING AV REDSKAP/SPILL
Water.

SÄKERHETSDATA

VOC-nivå:	28 g/l
VOC färdigmix:	29 g/l
VOC-kategori:	A/a
VOC-gräns:	30 g/l
Anmärkningar om säkerhet:	Consult Safety Data Sheet and Safety Information printed on the can.

HÅLLBARHET
Minimum of 2 years from date of production when kept in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Utgivningsdatum: 22/06/2026

Tillgängliga färger och förpackningsstorlekar: Se respektive produktsida på www.rust-oleum.eu för en översikt över tillgängliga färger och förpackningsstorlekar.

Förbehåll: Informationen i detta produktdatablad är korrekt så långt vi känner till och ges i god tro men utan garanti. Vi förutsätter att användaren självständigt har tagit ställning till lämpligheten av våra produkter för hans eller hennes egna syften. Under inga omständigheter är Rust-Oleum Europe ansvarigt för indirekta skador eller följdskador. Produkterna ska förvaras, hanteras och användas under förhållanden som överensstämmer med Rust-Oleum Europes rekommendationer i den senaste utgåvan av produktdatabladet. Det är användarens ansvar att säkerställa att han/hon har den aktuella utgåvan. Senaste utgåvan av produktdatabladet kan erhållas kostnadsfritt från www.rust-oleum.eu eller vår kundtjänst. Rust-Oleum Europe förbehåller sig rätten att ändra egenskaperna i sina produkter utan föregående avisering.

Rust-Oleum Netherlands B.V.
Europalaan 9
5232 BC 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu