

Quality Paints since 1845  
**MATHYS**<sup>®</sup>



## PARACEM<sup>®</sup> DECO SOFT

# High-quality semi-matt interior wall paint

- Excellent flow
- Good mechanical resistance against rubbing
- Smooth semi-matt aspect
- Closed coating structure, washable
- High covering power

# PARACEM® DECO SOFT

## DESCRIPTION

Paracem® Deco Soft is a waterborne acrylic paint for interior application.

## RECOMMENDED USE

Decorative and satin matt finishing for indoor walls and ceilings.  
Applicable on most substrates (plaster, bricks, concrete, etc.) as well on glass fibre.

## TECHNICAL DATA

Density (g/cm <sup>3</sup> ):	1,33 - 1,37 (white - wit - blanc)
Gloss Level:	Matt,Semi-Matt
Gloss level at 60°:	Satin matt: 5-8%
Gloss level at 85°:	Satin matt: 15-20%
Solids Content in weight:	52 - 54% ( white - wit - blanc)
Solids content in volume:	38 - 40% white - wit - blanc)
Wet Scrub Resistance (EN 13300):	Class 1 (<5 µm abrasion at 200 strokes)

## DRY TIMES BY 20° C/RH 50%

Touch dry:	1 hour
Dry to recoat:	2 hours
Fully cured:	2 days

## RECOMMENDED WET FILM THICKNESS

140 µm

## RECOMMENDED DRY FILM THICKNESS

55 µm

## THEORETICAL CONSUMPTION

7 - 9 m<sup>2</sup>/l per coat

## PRACTICAL CONSUMPTION

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

## SURFACE PREPARATION

The surface must be dry and free of dust and grease. You can paint Paracem® Deco Soft directly over clean, old layers of paint that are still in good condition and onto surfaces that are not too porous.

You must treat porous surfaces with Paracem® Deco Primer first. Highly porous surfaces, smooth plaster, and water-resistant plasterboard must be impregnated with Pegafix first. Nicotine and water stains must be isolated first with Pegamat® RL or Zinsser primers Bulls Eye 123 or 123 Plus.

Unpainted woodwork must be treated appropriately first and a priming coat must be applied (e.g. Fassiprim Aqua or Zinsser primers Bulls Eye 123 or 123 Plus).

Metal objects without rust spots are to be pre-treated with Pegalink®, or Zinsser primers Bulls Eye 123.

On glass fibre, apply preferably first a coat of Paracem® Deco Primer or Zinsser primers Bulls Eye 123 or 123 Plus before finishing with 2 coats of Paracem® Deco Soft.

## DIRECTIONS FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

## APPLICATION CONDITIONS

> 5°C, < 80% R.H.

## APPLICATION & THINNING: BRUSH

Apply undiluted.

## APPLICATION & THINNING: ROLLER

Apply undiluted.

## APPLICATION & THINNING: AIRLESS SPRAY

Nozzle: 013 - 019 / Pressure: 160 - 200 bars.

## APPLICATION & THINNING: AIR-ATOMISED SPRAY

If required dilute with water.

## CLEANING OF EQUIPMENT / SPILLS

Water.

## SAFETY DATA

VOC level:	14 g/l
VOC readymix:	30 g/l
VOC category:	A/a
VOC limit:	30 g/l
Remarks regarding safety:	Consult Safety Data Sheet and Safety Information printed on the can.

## SHELF LIFE

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 07/02/2025

**Available colours & pack sizes:** Please refer to the respective product page on [www.rust-oleum.eu](http://www.rust-oleum.eu) for an overview of actual available colours and pack sizes.

**Disclaimer:** The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from [www.rust-oleum.eu](http://www.rust-oleum.eu) or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

**Rust-Oleum Netherlands B.V.**  
Zilverenberg 16  
5234 GM 's-Hertogenbosch  
The Netherlands  
T : +31 (0) 165 593 636  
F : +31 (0) 165 593 600  
info@rust-oleum.eu

**Tor Coatings Ltd (Rust-Oleum Industrial)**  
Shadon Way, Portobello Ind. Estate  
Birtley, Chester-le-Street  
DH3 2RE United Kingdom  
T : +44 (0)1914 113 146  
F : +44 (0)1914 113 147  
info@rust-oleum.eu

**Rust-Oleum France S.A.S.**  
38, av. du Gros Chêne  
95322 Herblay  
France  
T : +33(0) 130 40 00 44  
F : +33(0) 130 40 99 80  
info@rust-oleum.eu

**N.V. Martin Mathys S.A.**  
Kolenbergstraat 23  
3545 Zelem  
Belgium  
T : +32 (0) 13 460 200  
F : +32 (0) 13 460 201  
info@rust-oleum.eu