



PARACEM[®] DECO ULTRA CLEAN XTRA MATT

Excellent washable, extra-matt interior paint

- Excellent washability - Scrub resistance class 1
- Not glossy
- Limited writing effect in dark colors
- Good coverage
- Excellent flow

PARACEM® DECO ULTRA CLEAN XTRA MATT

BESKRIVELSE

Paracem® Deco Ultra Clean Xtra Matt is a highly washable alkaline emulsion, water-based interior wall paint with a lasting extra matt aspect. This decorative paint is available in white and in almost all possible colours, ranging from light to dark shades.

ANBEFALET BRUG

It's perfect for interior walls that need regular cleaning (e.g. children's rooms, kitchens, etc.). Suitable for most substrates (plaster, brick, concrete, etc.) in public and private buildings. No 'white marking' occurs with darker colours.

TEKNISK DATA

Tæthed:	1,5 (white - wit - blanc - weiß)
Glansgrad:	extra_matt
Glansgrad ved 85°:	Matt: 1%
Tørstofindhold i volumen:	43% (white - wit - blanc - weiß)
wet_scrub_resistance:	wsr_c1

TØRRETIDER VED 20°C/50% RELATIV LUFTFUGTIGHED

Berøringstør:	2 hours
Håndteringstør:	2 hours
Genbehandlingstør:	6 hours
Fuldt hærdet:	30 days

ANBEFALET VÅDFILMTYKKELSE

123 µm (white)

ANBEFALET TØRFILMTYKKELSE

53 µm (white)

TEORETISK FORBRUG

8 m²/l/coat

PRAKTISK FORBRUG

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

FORBEHANDLING AF OVERFLADEN

The surface must be dry and free of dust and grease.

You can paint Paracem® Deco Ultra Clean Xtra Matt directly over clean, old layers of paint that are still in good condition and onto surfaces that are not too porous.

You must treat porous surfaces with Paracem® Deco Primer first.

Highly porous surfaces, smooth plaster, and water-resistant plasterboard must be impregnated with Pegafix first.

Nicotine and water stains must be isolated first with Pegamat® RL or Zinsser primers Bulls Eye 123 or 123 Plus.

Unpainted woodwork must be treated appropriately first and a priming coat must be applied (e.g. Fassiprim Aqua or Zinsser primers Bulls Eye 123 or 123 Plus).

Metal objects without rust spots are to be pre-treated with Pegalink®, or Zinsser primers Bulls Eye 123.

On glass fibre, apply preferably first a coat of Paracem® Deco Primer or Zinsser primers Bulls Eye 123 or 123 Plus before finishing with 2 coats of Paracem® Deco Ultra Clean Xtra Matt.

When working in combination with a joint sealant, we recommend using our acrylic sealant Elastopro, which can be painted over after drying for at least 1 hour (20°C, 60% r.h.).

BRUGSANVISNING

To ensure homogeneity, thoroughly stir prior to use.

ANVENDELSBETINGELSER

> 8°C, < 80% R.H.

PÅFØRING OG FORTYNDING: PENSEL

Apply undiluted with brush with synthetic bristles.

PÅFØRING OG FORTYNDING: RULLE

Apply undiluted with a 10 mm micro fiber roller.

PÅFØRING OG FORTYNDING: LUFTLØS SPRØJTE

Nozzle: 0.017 - 0.021 / Pressure: 180 bars. Spraying is only recommended for white and colours from base P.

RENGØRING AF UDSKYR/SPILD

Clean the material with water and dispose of the residue appropriately.

BEMÆRKNINGER

Do not apply at temperatures below +8°C.

Not recommended for use in damp rooms (eg bathrooms).

Cleaning instructions: Remove the contamination as soon as possible. Most contamination can easily be removed with a soft, damp cloth. Use lukewarm water and a mild colourless detergent. Do not use abrasive cleaning products. Do not use excessive pressure when cleaning as this may result in removing paint which will leave marks.

For more serious contaminations first wipe the substrate with a soft damp cloth, then use Mathys Multi-cleaner (diluted 1:100). Allow to dry.

The best cleaning results are achieved after the Paracem® Deco Ultra Clean Xtra Matt has dried for minimum 30 days.

Although extensive evaluations have been undertaken to ensure the cleanability of the Paracem® Deco Ultra Clean Xtra Matt it might be possible that some contamination is difficult to remove and leaves traces.

Touching the paint may leave marks this is due to the matt nature of the product (the marks will be more visible on dark colours). There may be a shiny effect after drying of the first coats in colours that are made of D and TR bases.

SIKKERHEDSDATA

VOC-niveau:	10 g/l
VOC-færdigblanding:	10 g/l
VOC-kategori:	IIA/a
VOC-grænse:	30 g/l
Bemærkninger om sikkerhed:	Consult Safety Data Sheet and Safety Information printed on the can.

HOLDBARHED

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5 and 35°C.

Udstedelsesdato: 30/09/2024

Tilgængelige farver og pakningsstørrelser: Der henvises til den respektive produktside på www.rust-oleum.eu for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

Ansvarsfraskrivelse: Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europes anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra www.rust-oleum.eu eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu