



PARACEM[®] UNIVERSAL

Excellent covering universal paint for all outside work

- Matt universal paint for the outdoors
- Usable on all surfaces, such as bricks, gutters, wood, aluminium, etc.
- Colour and weatherproof for long-term protection
- Protection of the dried coat against contamination by mould
- Primer and finishing coat in one



PARACEM® UNIVERSAL

BESKRIVELSE

Excellent covering universal paint for outside work. Extremely suitable for durable decoration of woodwork, metal, bricks, plastic, concrete and more. New or already painted. Paracem® Universal is water-vapour permeable, water repellent, and requires minimum maintenance. Self-priming in most cases. Protects dry coating against contamination by mould. Paracem® Universal has a unique property, namely, the colour does not darken when the façade is wet.

ANBEFALET BRUG

Developed for all outside work, Paracem® Universal is ideal for applying to bricks, façade cladding, plaster, woodwork, plastic, galvanised metal, steel, concrete, and more. Paracem® Universal is self-priming and will immediately adhere to existing glossy surfaces without the need for sanding. A separate primer is unnecessary for most applications. Paracem® Universal provides excellent resistance against cracking, blistering, flaking, rain, and severe weather conditions. Two-layer system: Apply the first layer, which primes and seals the surface. The second layer completes the sealing process and provides additional moisture resistance and protection.

TEKNISK DATA

Tæthed:	1,25
Glansgrad:	Mat
Glansgrad ved 60°:	± 2%
Glansgrad ved 85°:	± 3%
Faststofindhold i vægt:	40%
Tørstofindhold i volumen:	40%
Vanddampermeabilitet:	Sd = 0,41 m

TØRRETIDER VED 20°C/50% RELATIV LUFTFUGTIGHED

Berøringstør:	1 h
Håndteringstør:	1 h
Genbehandlingstør:	1 h
Fuldt hærdet:	7 days

ANBEFALET VÅDFILMTRYKKELSE

100 µm per coat

ANBEFALET TØRFILMTRYKKELSE

40 µm per coat

TEORETISK FORBRUG

8-12 m²/l/coat

PRAKTISK FORBRUG

Practical coverage depends on many factors such as porosity and roughness of the substrate. A normal application consists of two layers. Apply an extra layer to areas with high exposure such as window sills and eaves.

FORBEHANDLING AF OVERFLADEN

The surface must be clean, dry and free of dust, dirt, grease, oil, wax, mould, glue residues, etc. Remove old non-adhering layers of paint. Clean the surface using ND14. Use AMW concentrate to remove algae and mould.

BRUGSANVISNING

Mix carefully before use.

ANVENDELSESBETINGELSER

> 10°C, < 85% R.H.

PÅFØRING OG FORTYNDING: PENSEL

Apply with brush with synthetic bristles.

PÅFØRING OG FORTYNDING: RULLE

Apply with synthetic roller.

PÅFØRING OG FORTYNDING: LUFTLØS SPRØJTE

Nozzle: 0.017 / Pressure: 140 - 170 bar

RENGØRING AF Udstyr/SPILD

Use lukewarm soapy water to clean off stains and materials.

BEMÆRKNINGER

Paracem® Universal is not recommended for use on floors, terraces, or horizontal surfaces that may be drenched in water or exposed to water for a long period of time. Before applying Paracem® Universal, we recommend that you thoroughly sand and degrease unweathered/new powder coatings and similar surfaces. Not suitable for application onto new plastisol or a new powder coating. These surfaces must be fully weathered. Paracem® Universal has no anti corrosive properties, so don't apply directly on ferrous metal surfaces, but always use an appropriate anticorrosive primer like Metal Cladding Primer. Specific substrates like enamelled bricks require an adhesion coat with diluted Noxyde.

SIKKERHEDSDATA

VOC-niveau:	35 g/l
VOC-færdigblanding:	35 g/l
VOC-kategori:	IIA/d
VOC-grænse:	130g/l (2010.)
Bemærkninger om sikkerhed:	Consult Safety Data Sheet and Safety Information printed on the can.

HOLDBARHED

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5 and 35°C.

Udstedelsesdato: 20/09/2024

Tilgængelige farver og pakningsstørrelser: Der henvises til den respektive produktside på www.rust-oleum.eu for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

Ansvarsfraskrivelse: Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europes anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra www.rust-oleum.eu eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T: +31 (0) 165 593 636
F: +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T: +44 (0)1914 113 146
F: +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T: +33(0) 130 40 00 44
F: +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T: +32 (0) 13 460 200
F: +32 (0) 13 460 201
info@rust-oleum.eu