Quality Paints since 1845
MATHYS®

PARASIL COMPACT

High build intermediate coat, siloxane resins

- Waterborne acrylic and polysiloxane resin
- Very thick coat with high covering power
- Application in 1 or 2 coats
- Direct application on well adhering, solid, even and uneven substrates
- Masks haircracking

PARASIL COMPACT

BESKRIVELSE
High build priming and intermediate coat based on waterborne acrylic and polysiloxane resins. To be used in combination with ParaSil®.

ANBEFALET BRUG
High build priming and intermediate coat for the protection and decoration of new or old exterior walls. Walls in masonry, concrete, hydraulic plasters. Masks hair-line cracking. Maintenance of old elastic paint coats and outer wall insulation.

ANBEFALET SYSTEM
On bare substrates or old well adhering and compatible undercoats: 1 coat of Parasil Compact: 500 to 700 g/m² plus 1 or 2 top coats of Parasil.
On very porous substrates: pretreatment with Primer 44 HS – 10 m²/l. Irregular surfaces: levelling with Pegacrete or with a suitable filler.

TEKNISK DATA

Tæthed:	1,54
Glansgrad:	Mat
Faststofindhold i vægt:	67 - 69 %
Tørstofindhold i volumen:	49 - 51 %

TØRRETIDER VED 20°C/50% RELATIV LUFTFUGTIGHED

Berøringstør:	4 hours
Genbehandlingstør:	24 hours

PRAKTISK FORBRUG

FORBEHANDLING AF OVERFLADEN
The substrate must be completely clean, dry and solid. In case of contamination by microorganisms the substrate must first be cleaned with a fungicide solution.

BRUGSANVISNING
To ensure homogeneity coating materials should be thoroughly stirred prior to use.

ANVENDELSESBETINGELSER
The works must be performed in conformity with DTU 59-1. Minimum temperature 7°C, maximum 30 °C and maximum relative humidity 80%.
No condensation during drying time. Low temperatures and/or high relative humidity willextend the drying time. Do not apply on hot walls and in direct sunlight.

PÅFØRING OG FORTYNDING: PENSEL
Synthetic brushes for water dilutable paints

PÅFØRING OG FORTYNDING: RULLE
Polyamide rollers with 20 mm long hair or longer according to roughness.

RENGØRING AF UDSTYR/SPILD
Water.

SIKKERHEDSDATA

VOC-niveau:	35 g/l
VOC-færdigblanding:	35 g/l
VOC-kategori:	A/c
VOC-grænse:	40 g/l
Bemærkninger om sikkerhed:	Consult safety data sheet and Safety information printed on the can.

HOLDBARHED
Minimum of 1 year from date of production in unopened original cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 7° and 30°C.

Udstedelsesdato: 08/09/2022

Tilgængelige farver og pakningsstørrelser: Der henvises til den respektive produktside på www.rust-oleum.eu for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

Ansvarsfraskrivelse: Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europes anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra www.rust-oleum.eu eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu