



PLASTOPAN LATEX

White putty filler

- Easy to apply
- Easy to sand
- Can be applied on alkaline substrates

PLASTOPAN LATEX

DESCRIPTION

Water based extra white putty filler, very elastic and flexible.

RECOMMENDED USE

For equalising inside walls before applying a latex coating.

TECHNICAL DATA

Density (g/cm³):	± 1,9
Gloss Level:	Matt
Solids Content in weight:	± 80 %
Solids content in volume:	± 63 %

RECOMMENDED WET FILM THICKNESS

± 1,6 mm

RECOMMENDED DRY FILM THICKNESS

± 1,0 mm

THEORETICAL CONSUMPTION

± 3 kg/m²

PRACTICAL CONSUMPTION

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application

SURFACE PREPARATION

Clean the substrate thoroughly. Remove old and loose coating layers. Do not apply on powdering and chalking layers. Can be applied without applying a primer.

DIRECTIONS FOR USE

Apply in a dry and well-ventilated area.
Apply without thinning using a putty knife.

APPLICATION CONDITIONS

Apply in a dry and well-ventilated area.

CLEANING OF EQUIPMENT / SPILLS

Water.

REMARKS

Apply Plastopan Latex in thin layers.

SAFETY DATA

VOC level:	15.2 g/l
Remarks regarding safety:	Consult Safety Data Sheet and Safety Information printed on the can.

SHELF LIFE

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° and 35°C.

Date issued: 07/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu