



SECCO® HYDRO CREME

Pasty hydrophobic substance.

- Permeable to water vapour
- Practically invisible
- Negligible volatility
- Solvent-free
- Good alkali resistance



SECCO® HYDRO CREME

BESKRIVELSE

A pasty, water-based hydrophobic substance specially developed to make mineral surfaces and mostly non-porous concrete durably water-repellent. This is made possible thanks to its high viscosity and long contact time, allowing it to achieve a high level of penetration. For use on horizontal, vertical and overhead surfaces.

ANBEFALET BRUG

For making brick, concrete, fibre cement, sandlime brick, joint mortars, aerated concrete etc. water-repellent.

TEORETISK FORBRUG

0,1 - 0,4 kg/m²

PRAKTIKSK FORBRUG

Dependent on many factors, such as porosity and roughness of the substrate and material losses during application.

FORBEHANDLING AF OVERFLADEN

The surface should be clean, dry, and free of dirt and grease.

BRUGSANVISNING

Before use, shake up and stir well to ensure a good degree of homogeneity.

ANVENDELSESBETINGELSER

> 5°C, < 80% R.H.

RENGØRING AF UDSTYR/SPILD

Water.

BEMÆRKninger

The surface should be free of dust and grease. Mortar in poor condition must be restored before application of this product. Apply in a single layer from the bottom of the surface to the top, keeping the porosity of the surface in mind. Protect surrounding materials, such as scaffolding, windows and plants, during application. Apply using a brush roller or airless spray.

HOLDBARHED

Minimum of 1 year from production date, provided it is stored in the unopened original packaging, in a dry, well-ventilated space, away from direct sunlight, at a temperature between 5° and 30°C.

Udstedelsesdato: 07/02/2025

Tilgængelige farver og pakningsstørrelser: Der henvises til den respektive produktside på www.rust-oleum.eu for en oversigt over aktuelle tilgængelige farver og pakningsstørrelser.

Ansvarsfraskrivelse: Oplysningerne heri er efter vores bedste overbevisning korrekte, og er afgivet i god tro, men uden garanti. Brugeren vil blive anset for at selvstændigt at have bekræftet egnetheden af vores produkter til hans/hendes egen særlige formål. Rust-Oleum Europa kan under ingen omstændigheder holdes ansvarlig for følgeskader eller hændelige skader. Produkterne skal opbevares, håndteres og anvendes under forhold, der er i overensstemmelse med Rust-Oleum Europes anbefalinger beskrevet i den nyeste udgave af databladet. Det er brugernes ansvar at sikre, at de har den opdaterede udgave. De nyeste udgaver af datablade kan downloades gratis fra www.rust-oleum.eu eller tilsendes på anmodning til vores kundeservice. Rust-Oleum Europe forbeholder sig ret til at ændre egenskaberne for sine produkter uden forudgående varsel.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zellem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu