



SECCO[®] HYDRO CREME

Pasty hydrophobic substance.

- Permeable to water vapour
- Practically invisible
- Negligible volatility
- Solvent-free
- Good alkali resistance



SECCO® HYDRO CREME

DESCRIPTION

A pasty, water-based hydrophobic substance specially developed to make mineral surfaces and mostly non-porous concrete durably water-repellent. This is made possible thanks to its high viscosity and long contact time, allowing it to achieve a high level of penetration. For use on horizontal, vertical and overhead surfaces.

RECOMMENDED USE

For making brick, concrete, fibre cement, sandlime brick, joint mortars, aerated concrete etc. water-repellent.

THEORETICAL CONSUMPTION

0,1 - 0,4 kg/m²

PRACTICAL CONSUMPTION

Dependent on many factors, such as porosity and roughness of the substrate and material losses during application.

SURFACE PREPARATION

The surface should be clean, dry, and free of dirt and grease.

DIRECTIONS FOR USE

Before use, shake up and stir well to ensure a good degree of homogeneity.

APPLICATION CONDITIONS

> 5°C, < 80% R.H.

CLEANING OF EQUIPMENT / SPILLS

Water.

REMARKS

The surface should be free of dust and grease. Mortar in poor condition must be restored before application of this product. Apply in a single layer from the bottom of the surface to the top, keeping the porosity of the surface in mind. Protect surrounding materials, such as scaffolding, windows and plants, during application. Apply using a brush roller or airless spray.

SHELF LIFE

Minimum of 1 year from production date, provided it is stored in the unopened original packaging, in a dry, well-ventilated space, away from direct sunlight, at a temperature between 5° and 30°C.

Date issued: 07/02/2025

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu