



SECCO® SUPER

Water repellent product

- Does not change the color of the substrate
- Colorless
- Water vapour permeable (breathing)
- Water repellent
- May be applied on dry recent masonry

SECCO® SUPER

DESCRIPTION

Water repellent product based on polysiloxanes.

RECOMMENDED USE

Water repellent treatment of porous walls (bricks, concrete, cement, etc.).

TECHNICAL DATA

Density (g/cm³):	± 0,8
Solids Content in weight:	± 5 %
Solids content in volume:	± 5 %

THEORETICAL CONSUMPTION

1 - 4 m²/l

PRACTICAL CONSUMPTION

Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application

SURFACE PREPARATION

Clean and dust off the outside walls that are sufficiently dry. Cracks and fissures must be filled up first.

DIRECTIONS FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

APPLICATION CONDITIONS

Dry weather, outside walls to be as dry as possible. > 5°C, < 80% R.H.

APPLICATION & THINNING: BRUSH

Apply undiluted until saturation (= wet outlook during a few seconds); it is advisable to apply a second coat within 15 minutes to obtain an optimum impregnation.

APPLICATION & THINNING: ROLLER

Apply with woollen roller with long hairs. Do not dilute.

APPLICATION & THINNING: AIRLESS SPRAY

Not recommended.

APPLICATION & THINNING: AIR-ATOMISED SPRAY

Not recommended. Can be flowed on the substrate with hand pressure equipment after removing the nozzle.

CLEANING OF EQUIPMENT / SPILLS

White spirit.

REMARKS

- Non-porous surfaces (glass, blue stone, varnished brick, etc.) must be protected from spray mist or spatters of Secco.
- Apply Secco only on non-painted mineral or cement containing substrates. The substrate has to be porous.
- Can be recovered with Murfill or Paracem.

SAFETY DATA

VOC level:	790 g/l
Remarks regarding safety:	Consult Safety Data Sheet and Safety Information printed on the can.

SHELF LIFE

Minimum of 2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5°C and 35°C.

Date issued: 12/06/2023

Available colours & pack sizes: Please refer to the respective product page on www.rust-oleum.eu for an overview of actual available colours and pack sizes.

Disclaimer: The information contained herein is to the best of our knowledge true and accurate and is given in good faith but without warranty. The user will be deemed to have satisfied him/herself independently as to the suitability of our products for his/her own particular purpose. In no event shall Rust-Oleum Europe be liable for consequential or incidental damages. Products must be stored, handled, and applied under conditions complying with Rust-Oleum Europe recommendations detailed within the latest copy of the product data sheet. It is the users responsibility to ensure that they have the current copy. Latest copies of the product data sheet is available for free and downloadable from www.rust-oleum.eu or upon a request to our Customer Services department. Rust-Oleum Europe reserves the right to change the properties of its' products without prior notification.

Rust-Oleum Netherlands B.V.
Zilverenberg 16
5234 GM 's-Hertogenbosch
The Netherlands
T : +31 (0) 165 593 636
F : +31 (0) 165 593 600
info@rust-oleum.eu

Tor Coatings Ltd (Rust-Oleum Industrial)
Shadon Way, Portobello Ind. Estate
Birtley, Chester-le-Street
DH3 2RE United Kingdom
T : +44 (0)1914 113 146
F : +44 (0)1914 113 147
info@rust-oleum.eu

Rust-Oleum France S.A.S.
38, av. du Gros Chêne
95322 Herblay
France
T : +33(0) 130 40 00 44
F : +33(0) 130 40 99 80
info@rust-oleum.eu

N.V. Martin Mathys S.A.
Kolenbergstraat 23
3545 Zelem
Belgium
T : +32 (0) 13 460 200
F : +32 (0) 13 460 201
info@rust-oleum.eu