Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758



SAFETY DATA SHEET

Cachemire Beton Primer

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : Cachemire Beton Primer

Product description : Paint Primer
Product type : Liquid.

UFI : P7A1-20UK-E00X-C4ST

1.2 Relevant identified uses of the substance or mixture and uses advised against

	Identified uses	
Consumer use Industrial use Professional use		

Uses advised against	Reason	
None identified.	-	

1.3 Details of the supplier of the safety data sheet

RUST-OLEUM EUROPE

Martin Mathys NV, Kolenbergstraat 23, B-3545 Zelem, Belgium

Telephone no.: +32 (0) 13 460 200

Fax no.: +32 (0) 13 460 201

Tor Coatings Limited

Unit 21, White Rose Way, Follingsby Park, Gateshead, Tyne & Wear, NE10 8YX United Kingdom

Telephone no.: +44 (0) 191 4106611

Fax no.: +44 (0) 191 4920125 enquiries@tor-coatings.com

e-mail address of person

: rpmeurohas@rustoleum.eu

responsible for this SDS

1.4 Emergency telephone number

National advisory body/Poison Centre

Supplier

Telephone number United Kingdom: : +44 870 8200418 / +44 2038073798

Great Britain

Hours of operation : 24 / 7

Date of issue/Date of revision : 23/08/2022 Date of previous issue : 23/08/2022 Version : 4.01 1/16

Cachemire Beton Primer

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Not classified.

The product is not classified as hazardous according to Regulation (EC) 1272/2008 as amended.

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements

: No signal word. Signal word

Hazard statements : No known significant effects or critical hazards.

Precautionary statements

: P103 - Read carefully and follow all instructions. General

P102 - Keep out of reach of children.

P101 - If medical advice is needed, have product container or label at hand.

Prevention : Not applicable. : Not applicable. Response : Not applicable. **Storage**

: P501 - Dispose of contents and container in accordance with all local, regional, **Disposal**

national and international regulations.

Supplemental label

elements

: EUH208 - Contains 1,2-benzisothiazol-3(2H)-one and reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one

[EC no. 220-239-6] (3:1). May produce an allergic reaction.

EUH210 - Safety data sheet available on request.

EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed.

Do not breathe spray or mist.

Supplemental label elements : Detergents -Regulation (EC) No

907/2006

: Not applicable.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and

articles

: Not applicable.

Special packaging requirements

Containers to be fitted

with child-resistant

: Not applicable.

fastenings

Tactile warning of danger : Not applicable.

2.3 Other hazards

Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

Other hazards which do

: None known.

not result in classification

Date of issue/Date of revision Date of previous issue : 23/08/2022 : 23/08/2022 Version : 4.01 2/16 Cachemire Beton Primer

SECTION 3: Composition/information on ingredients

3.2 Mixtures : Mixture

United Kingdom: Great Britain

Product/ingredient name	Identifiers	%	Classification	Specific Conc. Limits, M-factors and ATEs	Туре
1,2-benzisothiazol-3(2H)- one	REACH #: 01-2120761540-60 EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0,05	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 2, H411	ATE [Oral] = 490 mg/kg ATE [Inhalation (vapours)] = 0,5 mg/l Skin Sens. 1, H317: C ≥ 0,05% M [Acute] = 1	[1]
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	REACH #: 01-2120764691-48 CAS: 55965-84-9 Index: 613-167-00-5 List #: 611-341-5	<0,0015	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	ATE [Oral] = 64 mg/kg ATE [Dermal] = 92,4 mg/kg ATE [Inhalation (dusts and mists)] = 0,171 mg/l Skin Corr. 1B, H314: $C \ge 0,6\%$ Skin Irrit. 2, H315: 0,06% $\le C < 0,6\%$ Eye Dam. 1, H318: $C \ge 0,6\%$ Eye Irrit. 2, H319: 0,06% $\le C < 0,6\%$ Skin Sens. 1, H317: $C \ge 0,0015\%$ M [Acute] = 100 M [Chronic] = 100	[1]
			See Section 16 for the full text of the H statements declared above.		

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

<u>Type</u>

[1] Substance classified with a health or environmental hazard

List numbers have no legal significance.

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

Eye contact

: Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.

Inhalation

: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.

Date of issue/Date of revision : 23/08/2022 Date of previous issue : 23/08/2022 Version : 4.01 3/16

Cachemire Beton Primer

SECTION 4: First aid measures

Skin contact

: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.

Ingestion

: Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.

Protection of first-aiders

: No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact: No specific data.Inhalation: No specific data.Skin contact: No specific data.Ingestion: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician

: Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

Specific treatments: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing

media

: Use an extinguishing agent suitable for the surrounding fire.

Unsuitable extinguishing

media

: Do not use water jet.

5.2 Special hazards arising from the substance or mixture

Hazards from the substance or mixture

: In a fire or if heated, a pressure increase will occur and the container may burst.

Hazardous combustion products

 Decomposition products may include the following materials: metal oxide/oxides

5.3 Advice for firefighters

Special protective actions for fire-fighters

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to European standard EN 469 will provide a basic level of protection for chemical incidents.

Additional information: No unusual hazard if involved in a fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

Date of issue/Date of revision : 23/08/2022 Date of previous issue : 23/08/2022 Version : 4.01 4/16

Cachemire Beton Primer

SECTION 6: Accidental release measures

For emergency responders: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

Small spill

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

Stop leak if without risk. Move containers from spill area. Prevent entry into sewers. water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment. See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance.

7.1 Precautions for safe handling

Protective measures

Advice on general occupational hygiene

- : Put on appropriate personal protective equipment (see Section 8).
- : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities

Do not store below the following temperature: 0°C (32°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available. **Industrial sector specific** : Not available.

solutions

Date of issue/Date of revision : 23/08/2022 : 23/08/2022 Version : 4.01 5/16 Date of previous issue

Cachemire Beton Primer

SECTION 8: Exposure controls/personal protection

The information in this section contains generic advice and guidance. Information is provided based on typical anticipated uses of the product. Additional measures might be required for bulk handling or other uses that could significantly increase worker exposure or environmental releases.

8.1 Control parameters

Occupational exposure limits

Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Reference should be made to monitoring standards, such as the following: European Standard EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) European Standard EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) European Standard EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Type	Exposure	Value	Population	Effects
1,2-benzisothiazol-3(2H)-one	DNEL	Long term Inhalation	6,81 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	1,2 mg/m³	General population	Systemic
	DNEL	Long term Dermal	0,966 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	0,345 mg/ kg bw/day	General population	Systemic
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	DNEL	Long term Inhalation	0,02 mg/m³	Workers	Local
(- /	DNEL	Short term Inhalation	0,04 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	0,02 mg/m ³	General population	Local
	DNEL	Short term Inhalation	0,04 mg/m ³		Local
	DNEL	Long term Oral	0,09 mg/ kg bw/day	General population	Systemic
	DNEL	Short term Oral	0,11 mg/ kg bw/day	General population	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
titanium dioxide	Fresh water	0,127 mg/l	-
	Marine	>1 mg/l	-
	Sewage Treatment Plant	>100 mg/l	-
	Fresh water sediment	>1000 mg/kg	-
	Marine water sediment	>100 mg/kg	-
	Soil	100 mg/kg	-
	Marine water	0,0184 mg/l	-
	Fresh water	0,184 mg/l	-

8.2 Exposure controls

Date of issue/Date of revision : 23/08/2022 Date of previous issue : 23/08/2022 Version : 4.01 6/16

Cachemire Beton Primer

SECTION 8: Exposure controls/personal protection

Appropriate engineering controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. Use eye protection according to EN 166. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields.

Skin protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. > 8 hours (breakthrough time): nitrile rubber (0.5mm) gloves.

The recommendation for the type or types of glove to use when handling this product is based on information from the following source: EN374. The user must check that the final choice of type of glove selected for handling this product is the most appropriate and takes into account the particular conditions of use, as included in the user's risk assessment.

Body protection

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product. Recommended: Wear overalls or long sleeved shirt. (EN 467)

Other skin protection

: Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection

Based on the hazard and potential for exposure, select a respirator that meets the appropriate standard or certification. Respirators must be used according to a respiratory protection program to ensure proper fitting, training, and other important aspects of use. Recommended: organic vapour (Type A) and particulate filter (EN 140).

Environmental exposure

controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

9.1 Information on basic physical and chemical properties

Physical state : Liquid. [Paste.]

Colour White. **Odour** Odourless.

Date of issue/Date of revision : 23/08/2022 : 23/08/2022 Version: 4.01 7/16 Date of previous issue

Cachemire Beton Primer

SECTION 9: Physical and chemical properties

: Not available. **Odour threshold**

Melting point/freezing point

Initial boiling point and

boiling range

: >100°C (>212°F) [Literature]

Flammability (solid, gas) : Non-flammable in the presence of the following materials or conditions: open

flames, sparks and static discharge, heat and shocks and mechanical impacts.

Nonflammable, but will burn on prolonged exposure to flame or high

temperature.

: 0°C [Literature]

Lower and upper explosion

limit

: Not available.

Flash point Not relevant due to nature of the product. **Auto-ignition temperature** Not relevant due to nature of the product.

Decomposition temperature

: Not available.

: 10 [Conc. (% w/w): 100%] [OECD 122] pН

pH: Justification : Not available. **Viscosity** : Not available.

Solubility(ies)

Media	Result	
cold water	Soluble	
hot water	Soluble	
methanol	Very slightly soluble	
acetone	Very slightly soluble	

Solubility in water : Not available.

Partition coefficient: n-octanol/ : Not applicable.

water

Vapour pressure : 2,3 kPa (17,25 mm Hg) [Literature]

Evaporation rate : <1 (butyl acetate = 1) Relative density : 1,4 to 1,48 [DIN 53217]

Density : 1,4 to 1,48 g/cm³ [20°C (68°F)] [DIN 53217]

Vapour density : >1 [Air = 1]

: Non-explosive in the presence of the following materials or conditions: open **Explosive properties**

flames, sparks and static discharge and heat.

No unusual hazard if involved in a fire.

Oxidising properties

Particle characteristics

: Not available.

Median particle size : Not applicable.

SECTION 10: Stability and reactivity

: No specific test data related to reactivity available for this product or its ingredients. 10.1 Reactivity

10.2 Chemical stability : The product is stable.

10.3 Possibility of hazardous reactions : Under normal conditions of storage and use, hazardous reactions will not occur.

10.4 Conditions to avoid : No specific data.

10.5 Incompatible materials : No specific data.

Date of issue/Date of revision : 23/08/2022 : 23/08/2022 Version : 4.01 8/16 Date of previous issue

Cachemire Beton Primer

SECTION 10: Stability and reactivity

10.6 Hazardous decomposition products : Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
1,2-benzisothiazol-3(2H)- one	LC50 Inhalation Dusts and mists	Rat	0,11 mg/l	4 hours
	LC50 Inhalation Dusts and mists	Rat - Male, Female	0,5 mg/l	4 hours
	LD50 Oral	Rat - Male	490 mg/kg	-
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3: 1)	LC50 Inhalation Dusts and mists	Rat - Male, Female	0,171 mg/l	4 hours
•,	LD50 Dermal LD50 Oral	Rabbit Rat	92,4 mg/kg 64 mg/kg	-

Conclusion/Summary

: Based on available data, the classification criteria are not met.

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3:1)	490	N/A	N/A	0,5	N/A
	64	92,4	N/A	N/A	0,171

Irritation/Corrosion

Product/ingredient name	Result	Species	Score	Exposure	Observation
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3:	Eyes - Severe irritant	Rabbit	-	-	-
,	Skin - Severe irritant Skin - Severe irritant	Human Rabbit	-	0.01 Percent -	- 1 to 4 hours

Conclusion/Summary

Skin

: Based on available data, the classification criteria are not met.

Eyes

: Based on available data, the classification criteria are not met.

Respiratory

: Based on available data, the classification criteria are not met.

Sensitisation

9/16 Date of issue/Date of revision : 23/08/2022 : 23/08/2022 Version : 4.01 Date of previous issue

Cachemire Beton Primer

SECTION 11: Toxicological information

Product/ingredient name	Route of exposure	Species	Result
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3: 1)	skin	Guinea pig Guinea pig	Sensitising Sensitising

Conclusion/Summary

Skin : Based on available data, the classification criteria are not met.Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Carcinogenicity

It has been observed that the carcinogenic hazard of this product arises when respirable dust is inhaled in quantities leading to significant impairment of particle clearance mechanisms in the lung.

Conclusion/Summary: Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary: Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

Aspiration hazard

Not available.

Information on likely routes : Routes of entry anticipated: Oral, Inhalation. Routes of entry not anticipated: Dermal.

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Short term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Date of issue/Date of revision : 23/08/2022 Date of previous issue : 23/08/2022 Version : 4.01 10/16

Cachemire Beton Primer

SECTION 11: Toxicological information

Long term exposure

Potential immediate : Not available.

effects

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary: Based on available data, the classification criteria are not met.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

11.2 Information on other hazards

11.2.1 Endocrine disrupting properties

Not available.

11.2.2 Other information

Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
1,2-benzisothiazol-3(2H)-one	Acute EC50 0,11 mg/l	Algae	72 hours
	Acute EC50 0,067 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 0,9893 mg/l Marine water	Crustaceans - Opossum Shrimp	96 hours
	Acute EC50 2,94 mg/l Fresh water	Daphnia spec.	48 hours
	Acute LC50 2,18 mg/l Fresh water	Fish	96 hours
	Acute LC50 8 to 13 mg/l	Fish - Alburnus alburnus	96 hours
	Acute LC50 1,6 to 2,8 ppm Fresh water	Fish - Oncorhynchus mykiss	96 hours
	Chronic NOEC 90 mg/l	Aquatic plants - Phaseolus vulgaris	20 days
	Chronic NOEC 1,2 mg/l	Daphnia spec.	21 days
	Chronic NOEC 0,21 mg/l	Fish	28 days
	Chronic NOEL 0,0403 mg/l	Algae	72 hours
reaction mass of: 5-chloro- 2-methyl-4-isothiazolin- 3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol- 3-one [EC no. 220-239-6] (3: 1)	Acute EC50 0,037 mg/l Fresh water	Algae	48 hours
	Acute EC50 0,16 mg/l Fresh water	Daphnia spec.	48 hours
	Acute LC50 0,19 mg/l Fresh water	Fish	96 hours
	Acute NOEC 0,004 mg/l Marine water	Algae	48 hours
	Chronic NOEC 0,18 mg/l	Daphnia spec.	21 days
	Chronic NOEC 0,02 mg/l Fresh water	Fish	38 days

Conclusion/Summary

: Based on available data, the classification criteria are not met.

12.2 Persistence and degradability

Date of issue/Date of revision : 23/08/2022 Date of previous issue : 23/08/2022 Version : 4.01 11/16

Cachemire Beton Primer

SECTION 12: Ecological information

Product/ingredient name	Test	Result	Dose	Inoculum
1,2-benzisothiazol-3(2H)-one	OECD 303A	>90 % - Readily - 1 days	-	-
reaction mass of: 5-chloro-	OECD 301D	>60 % - Readily - 28 days	-	-
2-methyl-4-isothiazolin-				
3-one [EC no. 247-500-7]				
and 2-methyl-2H-isothiazol-				
3-one [EC no. 220-239-6] (3:				
1)				
	-	<50 % - 10 days	-	-

Conclusion/Summary

: This product has not been tested for biodegradation. Based on available data, the classification criteria are not met.

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3: 1)	-		Readily Readily

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
1,2-benzisothiazol-3(2H)-one reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H-isothiazol-3-one [EC no. 220-239-6] (3: 1)	-0.83 to 0.75	-	low low

12.4 Mobility in soil

Soil/water partition coefficient (Koc)

: Not available.

coefficient (Noc)

Mobility

: Nonvolatile liquid.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Endocrine disrupting properties

Not available.

12.7 Other adverse effects

No known significant effects or critical hazards.

Date of issue/Date of revision : 23/08/2022 Date of previous issue : 23/08/2022 Version : 4.01 12/16

Cachemire Beton Primer

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance.

13.1 Waste treatment methods

Product

Methods of disposal

- The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.
- **Hazardous waste**
- : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 2008/98/EC.

European waste catalogue (EWC)

Waste code	Waste designation
08 01 12	waste paint and varnish other than those mentioned in 08 01 11

Special precautions

: This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

ADR/RID	ADN	IMDG	IATA
Not regulated.	Not regulated.	Not regulated.	Not regulated.
-	-	-	-
-	-	-	-
-	-	-	-
No.	No.	No.	No.
	Not regulated	Not regulated.	Not regulated. Not regulated. Not regulated. - - - - - - - - - - - - -

user

14.6 Special precautions for : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

Date of issue/Date of revision : 23/08/2022 : 23/08/2022 Date of previous issue Version: 4.01 13/16

Cachemire Beton Primer

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Other EU regulations

VOC :

VOC for Ready-for-Use : IIA/h. Binding primers. EU limit value for this product : 30g/l (2010.)

Mixture This product contains a maximum of 30 g/l VOC.

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Air

Industrial emissions : Not listed

(integrated pollution prevention and control) -

Water

United Kingdom: Great Britain

UK (GB) /REACH

Annex XIV - List of substances subject to authorisation

Annex XIV

None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

Prior Informed Consent (PIC)

Not listed.

Persistent Organic Pollutants

Not listed.

Aerosol dispensers

Seveso Directive

This product is not controlled under the Seveso Directive.

Annex XVII - Restrictions : Not applicable.

on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

International regulations

Stockholm Convention on Persistent Organic Pollutants

List name	Ingredient name	Status
Not listed.		

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

List name	Ingredient name	Status
Not listed.		

CN code : 3209 10 00 00

Date of issue/Date of revision : 23/08/2022 Date of previous issue : 23/08/2022 Version : 4.01 14/16

Cachemire Beton Primer

SECTION 15: Regulatory information

Inventory list

Australia : Not determined.
Canada : Not determined.
China : Not determined.

Eurasian Economic Union: Russian Federation inventory: Not determined.

Japan : Japan inventory (CSCL): Not determined.

Japan inventory (ISHL): Not determined.

New Zealand : Not determined.
Philippines : Not determined.
Republic of Korea : Not determined.
Taiwan : Not determined.
Thailand : Not determined.
Turkey : Not determined.

United States : All components are active or exempted.

Viet Nam : Not determined.

15.2 Chemical safety

assessment

: This product contains substances for which Chemical Safety Assessments are still

required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms

: ATE = Acute Toxicity Estimate

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No.

1272/2008]

DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

EUH statement = CLP-specific Hazard statement

N/A = Not available

PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number

SGG = Segregation Group

vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]

Classification	Justification
Not classified.	

Full text of abbreviated H statements

United Kingdom: Great Britain

Full text of abbreviated H

statements

:	H301	Toxic if swallowed.
	H302	Harmful if swallowed.
	H310	Fatal in contact with skin.
	H314	Causes severe skin burns and eye damage.
	H315	Causes skin irritation.
	H317	May cause an allergic skin reaction.
	H318	Causes serious eye damage.
	H330	Fatal if inhaled.
	H400	Very toxic to aquatic life.
	H410	Very toxic to aquatic life with long lasting effects.
	H411	Toxic to aquatic life with long lasting effects.

Date of issue/Date of revision : 23/08/2022 Date of previous issue : 23/08/2022 Version : 4.01 15/16

Cachemire Beton Primer

SECTION 16: Other information

Full text of classifications [CLP/GHS]

Acute Tox. 2 ACUTE TOXICITY - Category 2
Acute Tox. 3 ACUTE TOXICITY - Category 3
Acute Tox. 4 ACUTE TOXICITY - Category 4

Aquatic Acute 1 SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1 Aquatic LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1

Chronic 1

Aquatic LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 2

Chronic 2

Eye Dam. 1 SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1

Skin Corr. 1B SKIN CORROSION/IRRITATION - Category 1B Skin Irrit. 2 SKIN CORROSION/IRRITATION - Category 2

Skin Sens. 1 SKIN SENSITISATION - Category 1 Skin Sens. 1A SKIN SENSITISATION - Category 1A

Date of printing

Date of issue/ Date of

: 23/08/2022 : 23/08/2022

revision

Date of previous issue

: 23/08/2022 : 4.01

Notice to reader

Version

IMPORTANT NOTE: The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.