Conforms to Regulation (EC) No. 1907/2006 (REACH), Annex II, as amended by UK REACH Regulation SI 2019/758

SAFETY DATA SHEET



Pegamat Aqua Isole

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier	
Product name	: Pegamat Aqua Isole
Product description	: Paint
Product type	: Liquid.
UFI	: XEM1-70Q2-600V-4P4Q

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses		
Consumer Industrial Professional		
Uses advised against	Reason	
None identified.	-	

1.3 Details of the supplier of the safety data sheet

RUST-OLEUM EUROPE

Martin Mathys NV, Kolenbergstraat 23, B-3545 Zelem, Belgium Telephone no.: +32 (0) 13 460 200 Fax no.: +32 (0) 13 460 201

Tor Coatings Limited Unit 21, White Rose Way, Follingsby Park, Gateshead, Tyne & Wear, NE10 8YX United Kingdom Telephone no.: +44 (0) 191 4106611 Fax no.: +44 (0) 191 4920125 enquiries@tor-coatings.com

e-mail address of person : rpmeurohas@rustoleum.eu responsible for this SDS

1.4 Emergency telephone number

National advisory body/Poison Centre

Supplier

Telephone number United Kingdom:: +44 870 8200418 / +44 2038073798Great BritainHours of operation: 24 / 7

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Product definition : Mixture

Classification according to UK CLP/GHS

Eye Irrit. 2, H319

The product is classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

See Section 16 for the full text of the H statements declared above.

See Section 11 for more detailed information on health effects and symptoms.

Date of issue/Date of revision	: 29/05/2024	Date of previous issue	: 14/02/2024	Version : 7	1/16

SECTION 2: Hazards identification

2.2 Label elements		
Hazard pictograms	:	
Signal word	:	Warning
Hazard statements	1	H319 - Causes serious eye irritation.
Precautionary statements		
General	:	 P103 - Read carefully and follow all instructions. P102 - Keep out of reach of children. P101 - If medical advice is needed, have product container or label at hand.
Prevention	4	P280 - Wear eye or face protection.
Response	4	Not applicable.
Storage	4	Not applicable.
Disposal	:	P501 - Dispose of contents and container in accordance with all local, regional, national and international regulations.
Supplemental label elements	:	EUH208 - Contains Octene, hydroformylation products, high-boiling and 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction. EUH211 - Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.
Supplemental label elements : Detergents - Regulation (EC) No 907/2006	:	Not applicable.
Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles	:	Not applicable.
Special packaging requirem	en	<u>ts</u>
Containers to be fitted with child-resistant fastenings	:	Not applicable.
Tactile warning of danger	:	Not applicable.
2.3 Other hazards		
Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII	:	This mixture does not contain any substances that are assessed to be a PBT or a vPvB.
Other hazards which do not result in classification	:	None known.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

: Mixture

Product/ingredient name	Identifiers	%	Classification	Туре
barium bis (dihydrogenorthophosphate)	REACH #: 01-2120762057-54 EC: 236-715-1 CAS: 13466-20-1 Index: 056-002-00-7	≤1,5	Acute Tox. 4, H302 Acute Tox. 4, H332 Eye Dam. 1, H318	[1]
C16-C18 fatty acid alcohol ethoxylate / propoxylate phosphate ester	CAS: 68649-29-6	≤1,4	Skin Irrit. 2, H315 Eye Dam. 1, H318	[1]
Alkanes, iso-, C11-13	REACH #: 01-2119456810-40 EC: 920-901-0 Index: 920-901-0	≤1	Asp. Tox. 1, H304 EUH066	[1]
hydrocarbons, C11-C12, iso- alkanes, <2% aromatics	REACH #: 01-2119472146-39 EC: 918-167-1	≤1	Flam. Liq. 3, H226 Asp. Tox. 1, H304 EUH066	[1]
Octene, hydroformylation products, high-boiling	REACH #: 01-2119486463-31 EC: 271-237-7 CAS: 68526-89-6	≤0,3	Skin Sens. 1B, H317	[1]
pyrithione zinc	REACH #: 01-2119511196-46 EC: 236-671-3 CAS: 13463-41-7 Index: 613-333-00-7	<0,01	Acute Tox. 3, H301 Acute Tox. 2, H310 Acute Tox. 2, H330 Eye Dam. 1, H318 Repr. 1B, H360D STOT RE 1, H372 Aquatic Acute 1, H400 (M=1000) Aquatic Chronic 1, H410 (M=10)	[1]
1,2-benzisothiazol-3(2H)-one	REACH #: 01-2120761540-60 EC: 220-120-9 CAS: 2634-33-5 Index: 613-088-00-6	<0,036	Acute Tox. 4, H302 Acute Tox. 2, H330 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)	[1]
			See Section 16 for the full text of the H statements declared above.	

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

This mixture contains ≥ 1% of titanium dioxide. The Annex VI classification of titanium dioxide does not apply to this mixture according to Note 10.

Occupational exposure limits, if available, are listed in Section 8.

SECTION 4: First aid measures

4.1 Description of first aid measures

- Eye contact
- : Immediately flush eves with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention.

SECTION 4: First ai	d measures
Inhalation	: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Skin contact	 Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Ingestion	: Wash out mouth with water. Remove dentures if any. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Protection of first-aiders	: No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

4.2 Most important symptoms and effects, both acute and delayed

Over-exposure signs/symptoms

Eye contact	: Adverse symptoms may include the following: pain or irritation watering redness
Inhalation	: No specific data.
Skin contact	: No specific data.
Ingestion	: No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

Notes to physician	 Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
Specific treatments	: No specific treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
5.2 Special hazards arising f	rom the substance or mixture
Hazards from the substance or mixture	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous combustion products	: Decomposition products may include the following materials: carbon dioxide carbon monoxide phosphorus oxides metal oxide/oxides

5.3 Advice for firefighters

SECTION 5: Firefighting measures

•	•
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.
Additional information	: No unusual hazard if involved in a fire.

SECTION 6: Accidental release measures

6.1 Personal precautions, pro	tective equipment and emergency procedures
For non-emergency personnel	: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.
For emergency responders	: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
6.2 Environmental precautions	: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
6.3 Methods and material for	containment and cleaning up
Small spill	: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	: Stop leak if without risk. Move containers from spill area. Approach the release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilt product. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
6.4 Reference to other sections	: See Section 1 for emergency contact information. See Section 8 for information on appropriate personal protective equipment.

See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

Protective measures	: Put on appropriate personal protective equipment (see Section 8). Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapour or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Advice on general occupational hygiene	: Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

SECTION 7: Handling and storage

7.2 Conditions for safe storage, including any incompatibilities

Do not store below the following temperature: 0°C (32°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations Industrial sector specific solutions

- : Not available.
- : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Biological exposure indices

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres -Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

DNELs/DMELs

Product/ingredient name	Туре	Exposure	Value	Population	Effects
Octene, hydroformylation products, high-boiling	DNEL	Long term Oral	25 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	50 mg/kg bw/day	General population	Systemic
	DNEL	Long term Inhalation	87 mg/m ³	General population	Systemic
	DNEL	Long term Dermal	116,7 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	411,4 mg/ m ³	Workers	Systemic
1,2-benzisothiazol-3(2H)-one	DNEL	Long term Inhalation	6,81 mg/m³	Workers	Systemic
	DNEL	Long term Inhalation	1,2 mg/m³	General population	Systemic
	DNEL	Long term Dermal	0,966 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Dermal	0,345 mg/ kg bw/day	General population	Systemic

PNECs

Product/ingredient name	Compartment Detail	Value	Method Detail
Octene, hydroformylation products, high-	Fresh water	0,1 mg/l	-
boiling		_	
	Marine water	0,01 mg/l	-
	Sewage Treatment	100 mg/l	-
	Plant		
	Fresh water sediment	4000 mg/kg	-
	Marine water sediment	400 mg/kg	-
	Soil	1,25 mg/kg	-
pyrithione zinc	Fresh water	0,00009 mg/l	-
	Marine water	0,00009 mg/l	-
	Sewage Treatment	0,01 mg/l	-
	Plant		
	Marine water sediment	0,0095 mg/kg	-
	Fresh water sediment	0,0095 mg/kg	-
1,2-benzisothiazol-3(2H)-one	Fresh water	0,00403 mg/l	-
	Marine water	0,000403 mg/l	-
	Sewage Treatment	1,03 mg/l	-
	Plant		
	Fresh water sediment	0,0499 mg/kg dwt	-
	Marine water sediment	0,00499 mg/kg	-
		dwt	
	Soil	3 mg/kg dwt	-

SECTION 8: Exposure controls/personal protection

8.2 Exposure controls

Appropriate engineering controls	Good general ventilation should contaminants.	be sufficient to control worker exposure to airborne
Individual protection meas		
Hygiene measures	before eating, smoking and usir Appropriate techniques should b	e thoroughly after handling chemical products, ig the lavatory and at the end of the working period. be used to remove potentially contaminated clothing. fore reusing. Ensure that eyewash stations and workstation location.
Eye/face protection	assessment indicates this is nec gases or dusts. Use eye protect	an approved standard should be used when a risk cessary to avoid exposure to liquid splashes, mists, ion according to EN 166. If contact is possible, the rorn, unless the assessment indicates a higher splash goggles.

Skin protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals.

The breakthrough time must be greater than the end use time of the product.

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed.

Gloves should be replaced regularly and if there is any sign of damage to the glove material.

Always ensure that gloves are free from defects and that they are stored and used correctly.

The performance or effectiveness of the glove may be reduced by physical/chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

Hand protection

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated. > 8 hours (breakthrough time): nitrile rubber (0.5mm)

SECTION 8: Exposure controls/personal protection

	e recommendation for the type or types of glove to use who oduct is based on information from the following source: El eck that the final choice of type of glove selected for handl ost appropriate and takes into account the particular condit cluded in the user's risk assessment.	N374. The user must ing this product is the
Body protection	ersonal protective equipment for the body should be selected ing performed and the risks involved and should be approv fore handling this product. Recommended: (EN 467) Wea seved shirt.	ved by a specialist
Other skin protection	propriate footwear and any additional skin protection meas lected based on the task being performed and the risks inv proved by a specialist before handling this product.	
Respiratory protection	sed on the hazard and potential for exposure, select a res propriate standard or certification. Respirators must be us spiratory protection program to ensure proper fitting, trainir pects of use. Recommended: organic vapour filter (Type / 0)	ed according to a g, and other important
Environmental exposure controls	nissions from ventilation or work process equipment shoul sure they comply with the requirements of environmental p some cases, fume scrubbers, filters or engineering modifie uipment will be necessary to reduce emissions to acceptal	protection legislation. cations to the process

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature and pressure unless otherwise indicated.

Physical state	: Liquid.
Colour	: White.
Odour	: Characteristic.
Odour threshold	: Not available.
Melting point/freezing point	: 0°C [Literature]
Initial boiling point and boiling range	: >100°C (>212°F) [Literature]
Flammability (solid, gas)	: Non-flammable in the presence of the following materials or conditions: open flames, sparks and static discharge, heat and shocks and mechanical impacts. Non-flammable but will burn on prolonged exposure to flame or high temperature.
Lower and upper explosion limit	: Not available.
Flash point	: Not relevant due to nature of the product.
Auto-ignition temperature	: Not relevant due to nature of the product.
Decomposition temperature	: Not available.
рН	8 to 9 [Conc. (% w/w): 100%] [OECD 122]
pH : Justification	: Not available.
Viscosity	 Dynamic (room temperature): 4000 to 5000 mPa·s [ISO EN BS DIN 3219] Kinematic (room temperature): 2721 to 3472 mm²/s [calculated.] Kinematic (40°C): >20,5 mm²/s [calculated.]
Solubility(ies)	: · · · · · · · · · · · · · · · · · · ·

9.1 Information on basic physical and chemical properties

Media	Result	
cold water	Soluble	
hot water	Soluble	
methanol	Very slightly soluble	
acetone	Very slightly soluble	

Solubility in water

: Not available.

SECTION 9: Physical and chemical properties

Partition coefficient: n-octanol/ water	: Not applicable.
Vapour pressure	: 2,3 kPa (17,25 mm Hg) [Literature]
Evaporation rate	: <1 (butyl acetate = 1)
Relative density	: Not available.
Density	: 1,44 to 1,47 g/cm³ [20°C (68°F)] [DIN 53217]
Vapour density	: >1 [Air = 1]
Explosive properties	 Non-explosive in the presence of the following materials or conditions: open flames, sparks and static discharge and heat. No unusual hazard if involved in a fire.
Oxidising properties	: Not available.
Particle characteristics	
Median particle size	: Not applicable.

SECTION 10: Stability and reactivity				
10.1 Reactivity	: No specific test data related to reactivity available for this product or its ingredients.			
10.2 Chemical stability	: The product is stable.			
10.3 Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occur.			
10.4 Conditions to avoid	: No specific data.			
10.5 Incompatible materials	: No specific data.			
10.6 Hazardous decomposition products	: Under normal conditions of storage and use, hazardous decomposition products should not be produced.			

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
barium bis (dihydrogenorthophosphate)	LD50 Dermal	Rat	>2000 mg/kg	-
	LD50 Oral	Rat	300 to 2000 mg/ kg	-
C16-C18 fatty acid alcohol ethoxylate / propoxylate phosphate ester	LD50 Oral	Rat	>2000 mg/kg	-
pyrithione zinc	LC50 Inhalation Dusts and mists	Rat	140 mg/m³	4 hours
	LD50 Dermal	Rabbit	100 mg/kg	-
	LD50 Oral	Rat	177 mg/kg	-
1,2-benzisothiazol-3(2H)- one	LC50 Inhalation Dusts and mists	Rat	0,11 mg/l	4 hours
	LC50 Inhalation Dusts and mists	Rat - Male, Female	0,5 mg/l	4 hours
	LD50 Oral	Rat - Male	490 mg/kg	-

Conclusion/Summary

ed on available data, the classification criteria are not met.

SECTION 11: Toxicological information

5					
Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Pegamat Aqua Isole	40612,1	N/A	N/A	893,5	N/A
barium bis(dihydrogenorthophosphate)	500	N/A	N/A	11	N/A
pyrithione zinc	221	100	N/A	N/A	0,14
1,2-benzisothiazol-3(2H)-one	450	N/A	N/A	N/A	0,21

Irritation/Corrosion

Skin

: Based on available data, the classification criteria are not met.

Eyes : Causes serious eye irritation.

Respiratory : Based on available data, the classification criteria are not met.

Respiratory or skin sensitization

Product/ingredient name	Route of exposure	Species	Result
1,2-benzisothiazol-3(2H)-one	skin	Guinea pig	Sensitising
Skin	: Based on availat	ble data, the classification criteri	a are not met.
Respiratory	: Based on availab	ole data, the classification criteri	a are not met.
<u>Mutagenicity</u>			
Conclusion/Summary	: Based on availab	ole data, the classification criteri	a are not met.
Carcinogenicity			
Conclusion/Summary	: Based on availab	ole data, the classification criteri	a are not met.
Reproductive toxicity			
Conclusion/Summary	: Based on availab	ole data, the classification criteri	a are not met.
<u>Teratogenicity</u>			
Conclusion/Summary	: Based on availab	ole data, the classification criteri	a are not met.
Specific target organ toxicity	(single exposure)	<u>)</u>	

Not available.

Specific target organ toxicity (repeated exposure)

Product/ingredient name	Category	Route of exposure	Target organs
pyrithione zinc	Category 1	-	-

Aspiration hazard

Product/ingredient name	Result
Alkanes, iso-, C11-13	ASPIRATION HAZARD - Category 1
hydrocarbons, C11-C12, iso-alkanes, <2% aromatics	ASPIRATION HAZARD - Category 1

Information on likely routes of exposure	:	Routes of entry anticipated: Oral, Inhalation, Eyes. Routes of entry not anticipated: Dermal.
Potential acute health effects		
Eye contact	:	Causes serious eye irritation.
Inhalation	:	No known significant effects or critical hazards.
Skin contact	:	No known significant effects or critical hazards.
Ingestion	;	No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

SECTION 11: Toxico	SECTION 11: Toxicological information					
Eye contact	:	Adverse symptoms may include the following: pain or irritation watering redness				
Inhalation	:	No specific data.				
Skin contact	:	No specific data.				
Ingestion	:	No specific data.				
Delayed and immediate effect	<u>cts</u>	as well as chronic effects from short and long-term exposure				
Short term exposure						
Potential immediate effects	:	Not available.				
Potential delayed effects	:	Not available.				
Long term exposure						
Potential immediate effects	:	Not available.				
Potential delayed effects	:	Not available.				
Potential chronic health eff	ect	<u>s</u>				
Not available.						
Conclusion/Summary	:	Based on available data, the classification criteria are not met.				
General	:	No known significant effects or critical hazards.				
Carcinogenicity	:	No known significant effects or critical hazards.				
Mutagenicity	:	No known significant effects or critical hazards.				
Reproductive toxicity	:	No known significant effects or critical hazards.				
		-				

Other information

: Not available.

SECTION 12: Ecological information

12.1 Toxicity

Product/ingredient name	Result	Species	Exposure
C16-C18 fatty acid alcohol ethoxylate / propoxylate	Acute EC10 >500 mg/l	Micro-organism - Activated sludge	-
phosphate ester			
	Acute EC50 1 to 10 mg/l	Daphnia spec Daphnia Magna	
pyrithione zinc	Acute EC50 0,51 µg/l Marine water	Algae - Diatom - <i>Thalassiosira</i> pseudonana	96 hours
	Acute EC50 80 µg/l Fresh water	Crustaceans - Water flea - Chydorus sphaericus	48 hours
	Acute EC50 38 µg/l Fresh water	Crustaceans - Ostracod - Ilyocypris dentifera	48 hours
	Acute EC50 8,25 ppb Fresh water	Daphnia spec Water flea - Daphnia magna	48 hours
	Acute EC50 61 µg/l Fresh water	Daphnia spec Water flea - Daphnia magna - Nauplii	48 hours
	Acute LC50 2,68 ppb Fresh water	Fish - Fathead minnow - Pimephales promelas	96 hours
	Chronic EC10 0,36 µg/l Marine water	Algae - Diatom - <i>Thalassiosira</i>	96 hours
	Chronic NOEC 2,7 ppb Marine water	Daphnia spec Water flea - Daphnia magna	21 days
1,2-benzisothiazol-3(2H)-one	Acute EC50 0,11 mg/l	Algae - Algae	72 hours
,	Acute EC50 0,067 mg/l	Algae - Pseudokirchneriella subcapitata	72 hours
	Acute EC50 0,9893 mg/l Marine water	Crustaceans - Opossum Shrimp	96 hours
	Acute EC50 2,94 mg/l Fresh water	Daphnia spec Daphnia spec.	48 hours
ate of issue/Date of revision	: 29/05/2024 Date of previous issue	: 14/02/2024 Version	:7 1:

SECTION 12: Ecological information

	J		
	Acute LC50 2,18 mg/l Fresh water	Fish - Rainbow trout	96 hours
		(oncorhynchus mykiss)	
	Acute LC50 8 to 13 mg/l	Fish - Alburnus alburnus	96 hours
	Acute LC50 1,6 to 2,8 ppm Fresh water	Fish - Rainbow trout,donaldson	96 hours
		trout - Oncorhynchus mykiss	
	Chronic NOEC 90 mg/l	Aquatic plants - Phaseolus	20 days
	_	vulgaris	-
	Chronic NOEC 1,2 mg/l	Daphnia spec Daphnia spec.	21 days
	Chronic NOEC 0,21 mg/l	Fish - Rainbow trout	28 days
		(oncorhynchus mykiss)	
	Chronic NOEL 0,0403 mg/l	Àlgae - Álgae	72 hours
Conclusion/Summary	: Based on available data, the classifica	ation criteria are not met.	-

12.2 Persistence and degradability

Product/ingredient name	Test	Result	Dose	Inoculum
C16-C18 fatty acid alcohol ethoxylate / propoxylate phosphate ester	OECD 301B	>60 % - Readily - 28 days	-	-
1,2-benzisothiazol-3(2H)-one	OECD 303A	>90 % - Readily - 1 days	-	-

Conclusion/Summary : Based on available data, the classification criteria are not met.					
Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability		
C16-C18 fatty acid alcohol ethoxylate / propoxylate phosphate ester	-	-	Readily		
hydrocarbons, C11-C12, iso- alkanes, <2% aromatics	-	-	Inherent		
1,2-benzisothiazol-3(2H)-one	-	-	Readily		

12.3 Bioaccumulative potential

Product/ingredient name	LogPow	BCF	Potential
Octene, hydroformylation products, high-boiling	>3.8	-	High
pyrithione zinc 1,2-benzisothiazol-3(2H)-one	0,9 0,64	11 -	Low Low

12.4 Mobility in soil	
Soil/water partition coefficient (Koc)	: Not available.
Mobility	: Nonvolatile liquid.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects : No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance.

13.1 Waste treatment methods

Product

Methods of disposal	: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.		
Hazardous waste	: Yes.		
Waste catalogue			
Waste code	Waste designation		
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances		
Special precautions	: This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.		

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

user

14.6 Special precautions for : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Transport in bulk according to IMO instruments

: Not available.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture **UK (GB)/REACH**

Annex XIV - List of substances subject to authorisation **Annex XIV**

None of the components are listed above the relevant limit.

Substances of very high concern

None of the components are listed above the relevant limit.

SECTION 15: Regulatory information

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles

			_	
Product/ingredient name		%	Designation [Usage]	
Pegamat Aqua Isole		≥90	3	
Labelling	: Not applicab	le.		
Other EU regulations				
VOC	product labe	l and/or techi	e 2004/42/EC on VOC apply to this nical data sheet for further informatic	on.
VOC for Ready-for-Use Mixture	This product		nce coatings. EU limit value for this p naximum of 25 g/l VOC.	roduct : 140g/I (2010.)
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed			
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed			
Ozone depleting substance	<u>es</u>			
Not listed.				
Prior Informed Consent (PI Not listed.	<u>C)</u>			
Persistent Organic Pollutar Not listed.	<u>nts</u>			
Seveso Directive				
This product is not controlled u	under the Seves	o Directive.		
EU regulations				
Industrial emissions (integrated pollution prevention and control) - Air	: Not listed			
Industrial emissions (integrated pollution prevention and control) - Water	: Not listed			
International regulations				
Chemical Weapon Convention Not listed.	<u>on List Schedu</u>	<u>les I, II & III (</u>	<u>Chemicals</u>	
Montreal Protocol Not listed.				
Stockholm Convention on P Not listed.	ersistent Orga	nic Pollutan	<u>ts</u>	
Rotterdam Convention on P Not listed.	rior Informed C	onsent (PIC	2	
UNECE Aarhus Protocol on Not listed.	POPs and Heav	vy Metals		
CN code : 3209 10 00 Inventory list	00			
			44/00/0004	

SECTION 15: Regulatory information

J		,
Australia	:	At least one component is not listed.
Canada	:	At least one component is not listed.
China	:	At least one component is not listed.
Eurasian Economic Union	:	Russian Federation inventory: Not determined.
Japan	:	Japan inventory (CSCL): At least one component is not listed. Japan inventory (ISHL): Not determined.
New Zealand	:	Not determined.
Philippines	:	At least one component is not listed.
Republic of Korea	:	At least one component is not listed.
Taiwan	:	At least one component is not listed.
Thailand	:	At least one component is not listed.
Turkey	:	Not determined.
United States	:	At least one component is not listed.
Viet Nam	:	Not determined.
15.2 Chemical safety assessment	:	This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms	 ATE = Acute Toxicity Estimate GB CLP = UK CLP (EC No 1272/2008) on the Classification, Labelling and Packaging of Substances and Mixtures as amended by (EU Exit) Regulations 2019 No. 720 and amendments DMEL = Derived Minimal Effect Level DNEL = Derived No Effect Level EUH statement = GB CLP-specific Hazard statement N/A = Not available PBT = Persistent, Bioaccumulative and Toxic PNEC = Predicted No Effect Concentration RRN = REACH Registration Number SGG = Segregation Group
	SGG = Segregation Group vPvB = Very Persistent and Very Bioaccumulative

Procedure used to derive the classification

Classification	Justification
Eye Irrit. 2, H319	Calculation method

Full text of abbreviated H statements

H226	Flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H332	Harmful if inhaled.
H360D	May damage the unborn child.
H372	Causes damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.

Full text of classifications

SECTION 16: Other information

Acute Tox. 2	ACUTE TOXICITY - Category 2	
Acute Tox. 3	ACUTE TOXICITY - Category 3	
Acute Tox. 4	ACUTE TOXICITY - Category 4	
Aquatic Acute 1	SHORT-TERM (ACUTE) AQUATIC HAZARD - Category 1	
Aquatic Chronic 1	LONG-TERM (CHRONIC) AQUATIC HAZARD - Category 1	
Asp. Tox. 1	ASPIRATION HAZARD - Category 1	
Eye Dam. 1	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 1	
Eye Irrit. 2	SERIOUS EYE DAMAGE/EYE IRRITATION - Category 2	
Flam. Liq. 3	FLAMMABLE LIQUIDS - Category 3	
Repr. 1B	REPRODUCTIVE TOXICITY - Category 1B	
Skin Irrit. 2	SKIN CORROSION/IRRITATION - Category 2	
Skin Sens. 1A	SKIN SENSITISATION - Category 1A	
Skin Sens. 1B	SKIN SENSITISATION - Category 1B	
STOT RE 1	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 1	
Date of printing	: 29/05/2024	
Date of issue/ Date of revision	: 29/05/2024	
Date of previous issue	: 14/02/2024	
Version	: 7	

Notice to reader

IMPORTANT NOTE: The information in this Safety Data Sheet is based on the present state of knowledge and current legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications. The information contained in this data sheet (as may be amended from time to time) is not intended to be exhaustive and is presented in good faith and believed to be correct as of the date on which it is prepared. It is the user's responsibility to verify that this data sheet is current prior to using the product to which it relates. Persons using the information must make their own determinations as to the suitability of the relevant product for their purposes prior to use. Where those purposes are other than as specifically recommended in this safety data sheet, then the user uses the product at their own risk.

MANUFACTURER'S DISCLAIMER: the conditions, methods and factors affecting the handling, storage, application, use and disposal of the product are not under the control and knowledge of the manufacturer. Therefore the manufacturer does not assume responsibility for any adverse events which may occur in the handling, storage, application, use, misuse or disposal of the product and, so far as permitted by applicable law, the manufacturer expressly disclaims liability for any and all loss, damages and/or expenses arising out of or in any way connected to the storage, handling, use or disposal of the product. Safe handling, storage, use and disposal are the responsibility of the users. Users must comply with all applicable health and safety laws.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.